

# Convotherm flexx pro Countertop Twin Pan Electric Multi Pan

# **CFXP 101DS** - 58 LITRE CAPACITY

- 2 x 29 litre pan capacity
- 2 x 1/1 GN pan size
- 2 x 20dm<sup>2</sup> cooking surface
- 170mm depth pan
- Multi pan for cooking, frying, braising, grilling, searing, broiling and sous-vide cooking
- Independent automatic arm for lifting / lowering of baskets
- Automatic water filling system with accuracy of 1 decilitre
- Electromechanical tray tilting at variable speed
- 12" colour touch screen with intuitive controls
- Automatic and manual meal preparation mode with memory for 800 programs with 12 steps
- Multipoint core temperature probe
- · Integrated retractable hand shower



#### **Overall Construction**

- Base frame with 3mm 304 grade stainless steel
- Frame cover with 304 grade stainless steel
- Tray with 3mm 316 grade stainless steel
- Special sandwich design pan base
- Stainless steel SUPER BLOCK JPX 17 full area heat distribution system
- Robust double insulated cover with automatic lifting function
- Excessive steam exhaust on cover
- Integrated 230V / 16A socket
- Retractable switchboard panel on right pillar allowing integration of multiple pans in a single block

#### **Controls**

- Fast base preheating
- Temperature range from 30°C-250°C
- Accurate sensory measurement of temperature
- Liquid level gauge
- Integrated drainage in the tray bottom with automatic closure
- Preset technological procedures
- Automatic lowering of baskets allows operation with cover closed
- Safety sensor for basket arm detection
- · Fault messages shown on display
- Water pressure controller
- HACCP recording
- USB port for data backup

## Accessories

- Easy clean stainless steel surface
- · Easy services access from front and top sides
- Technical and service information on display





# Convotherm flexx pro Countertop Twin Pan Electric Multi Pan

# **CFXP 101DS** - 58 LITRE CAPACITY

#### **DIMENSIONS**

Width	1290 mm
Depth	850 mm
Height	500 mm
Weight	220kg

# CAPACITY

58 litre

#### PACKED DIMENSIONS

 Width
 1345 mm

 Depth
 960 mm

 Height
 720 mm

 Weight
 245kg

#### ELECTRICAL SUPPLY

415V, 3P+N+E, 50Hz, 32A


Energy consumption 23.3kW


### WATER CONNECTION


Inlet connection R ¾ Water outlet connection Ø 50


#### INSTALLATION CONDITIONS


(for precise installation instructions please refer to our installation manual)













- 1 Drain DN 50
- 2 Water connection
- 3 Flectric connection
- 4 Ethernet socket RJ 45
- 5 Ground

# MOFERT

## moffat.com.au moffat.co.nz

#### Australia moffat.com.au

## Moffat Pty Limited

# Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

### New South Wales

Telephone +61 2-8833 4111 nswsales@moffat.com.au

#### South Australia

Telephone +61 3-9518 3888 vsales@moffat.com.au

#### Queensland / Northern Territory

Telephone +61 7-3630 8600

qldsales@moffat.com.au

## Western Australia

Telephone +61 8-9413 2400 wasales@moffat.com.au

# New Zealand moffat.co.nz

# Moffat Limited

## Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6660 Facsimile +64 3-983 6660 sales@moffat.co.nz

## Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.CON.S.01.25



