

# Convotherm flexx pro Single Pan Electric Pressure Multi Pan

## **CFXP 151P** - 150 LITRE CAPACITY

- 150 litre single pan capacity
- 3 x 1/1 GN pan size
- 63dm<sup>2</sup> cooking surface
- 280mm depth pan
- Pressurised version for faster cooking results
- Multi pan for cooking, frying, braising, grilling, searing, broiling and sous-vide cooking
- Independent automatic arm for lifting / lowering of baskets
- Automatic water filling system with accuracy of 1 decilitre
- · Electromechanical tray tilting at variable speed
- 12" colour touch screen with intuitive controls
- Automatic and manual meal preparation mode with memory for 800 programs with 12 steps
- Multipoint core temperature probe
- · Integrated retractable hand shower



#### **Overall Construction**

- Base frame with 3mm 304 grade stainless steel
- Frame cover with 304 grade stainless steel
- Tray with 3mm 316 grade stainless steel
- Special sandwich design pan base
- Stainless steel SUPER BLOCK JPX 17 full area heat distribution system
- Robust double insulated cover with automatic lifting function
- Excessive steam exhaust on cover
- Integrated 230V / 16A socket
- Retractable switchboard panel on right pillar allowing integration of multiple pans in a single block

#### Controls

- Fast base preheating
- Temperature range from 30°C-250°C
- Pressurised cooking at 110°C
- Automatic cover locking / unlocking during pressure cooking
- Automatic overpressure and steam condensation reduction at end of cooking cycle with condensate drainage without water injection
- Accurate sensory measurement of temperature
- · Liquid level gauge

- Integrated drainage in the tray bottom with automatic closure
- Preset technological procedures
- Automatic lowering of baskets allows operation with cover closed
- Safety sensor for basket arm detection
- Fault messages shown on display
- · Water pressure controller
- HACCP recording
- USB port for data backup

#### Accessories

- Easy clean stainless steel surface
- Easy services access from front and top sides
- Technical and service information on display





# Convotherm flexx pro Single Pan Electric Pressure Multi Pan **CFXP 151P** - 150 LITRE CAPACITY

#### DIMENSIONS

 Width
 1651 mm

 Depth
 950 mm

 Height
 1050 mm

 Weight
 590kg

### CAPACITY

#### PACKED DIMENSIONS

 Width
 1765 mm

 Depth
 1010 mm

 Height
 1145 mm

 Weight
 615kg

#### ELECTRICAL SUPPLY

415V, 3P+N+E, 50Hz, 50A


Energy consumption 38.2kW Pressure 0.48 bar


#### WATER CONNECTION

Inlet connection R ¾ Water outlet connection Ø 50


#### INSTALLATION CONDITIONS

(for precise installation instructions please refer to our installation manual)









- 1 Drain DN 50
- 2 Water connection
- 3 Electric connection
- 4 Ethernet socket RJ 45
- 5 Ground

## MOFERT

#### moffat.com.au moffat.co.nz

#### Australia moffat.com.au

#### Moffat Pty Limited

#### Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

#### New South Wales

Telephone +61 2-8833 4111 nswsales@moffat.com.au

#### South Australia

Telephone +61 3-9518 3888 vsales@moffat.com.au

#### Queensland / Northern Territory

Telephone +61 7-3630 8600 qldsales@moffat.com.au

#### Western Australia

Telephone +61 8-9413 2400 wasales@moffat.com.au

## New Zealand moffat.co.nz

#### Moffat Limited

#### Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

#### Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.CON.S.01.25



