20TSERIES



E27T2/2 E27T2/2C

Technical data sheet for

E27T2 DOUBLE STACKED

Full Size Electric Convection Ovens TOUCH SCREEN CONTROL Double Stacked on a Stainless Steel Base Stand



Model E27T2/2C shown



E27T2/2 E27T2/2C

E27T2 ovens shall be Moffat electrically heated Turbofan convection ovens E.T.L. listed and NSF-4 listed. The ovens shall have a one piece porcelain enameled oven chamber, stainless top and sides and safe touch vented easy clean drop down door. Ovens shall have capacity for two full size sheet pans. The ovens shall have 2.8kW heating elements for 220-240V models or 2.5kW heating elements for 208V models. The ovens shall have a bi-directional single reversing fan system and feature a single halogen oven lamp. The oven shall feature a programmable Touch Screen menu controller. Ovens shall be fitted with a NEMA 6-15P cordset. Ovens shall be double stacked using Double Stacking Kits DSK2728T (adjustable feet option) or DSK2728TC (castor option). Units shall be supplied in 100% recyclable shipping packaging.

Double stack models are supplied as two individual ovens and a double stacking kit for field assembly.

E27T2/2 - Double stack with adjustable feet base stand E27T2/2C - Double stack with castor base stand

DOUBLE STACK FEATURES

- Two full size ovens
- 945mm width
- · Full stainless steel base stand
- Full stainless steel oven spacer frame
- Adjustable feet or castor models
- Guard rail for bottom oven

OVEN FEATURES (each)

- 2 460mm x 660mm / 18" x 26" full size sheet pan capacity
- 2 400mm x 600mm tray capacity
- 115mm tray spacing
- Touch Screen control
- Icon driven program menu
- USB port for program/icon updating
- Individual shelf timers
- Multi-stage programs
- Steam injection mode and manual injection
- Bi-directional reversing fan system
- 2.8kW heating
- 15A plug-in cordset fitted
- Vitreous enamel oven chamber
- Plug-in continuous oven door seal
- Safe-Touch vented drop down door
- Stay-Cool door handle
- Heavy-duty door hinges
- Easy clean door glass system
- Dual halogen oven lamps
- Dia. 180mm full stainless steel oven fan
- 2 oven wire racks supplied



20TSERIES

turbofan

E27T2/2 E27T2/2C

E27T2/2 E27T2/2C Full Size Electric Convection Ovens TOUCH SCREEN CONTROL Double Stacked on a Stainless Steel Base Stand

CONSTRUCTION - OVENS

Vitreous enameled fully welded oven chamber Stainless steel front, sides and top exterior Stainless steel oven fan baffle and oven vent Removable 2 position chrome plated wire side racks Oven racks chrome plated wire (2 supplied)

Stainless steel frame drop down hinged door 0.2" / 5mm thick door outer glass

0.2" / 5mm thick low energy loss door inner glass Heavy-duty counterbalanced door hinges Wear resistant powder coated welded door handle

Stainless steel control panel

Aluminised coated steel base and rear panels CONSTRUCTION - DOUBLE STACKING KIT

All stainless steel construction Welded $1\frac{1}{2}$ " and $1\frac{1}{4}$ " square tube front and rear frame base stand

4 adjustable feet on E27T2/2

4 dia. 3" / 76mm swivel castors with 2 front castors dual wheel and swivel lock on E27T2/2C $\,$

Stainless steel oven spacer frame

Stainless steel bottom oven vent extension

CONTROLS (each oven) 5.7" LED backlit touch screen Icon driven program menu

BMP image icon imports via USB port Temperature range 150-500°F / 50-260°C Individual shelf timers

Individual shelf timers Multi-stage programs

Over-temperature safety cut-out

CLEANING

Stainless steel top and sides continuous exterior panel

Vitreous enameled oven chamber

Fully removable chrome plated oven side racks

Removable stainless steel oven fan baffle

Full stainless steel oven fan

Easy clean door system with hinge out door inner glass (no tools required)

Removable plug-in oven door seal (no tools required)

SPECIFICATIONS

Electrical Requirements (each oven) 230-240V, 50Hz, 1P+N+E 3.0kW, 12A

15A cordset fitted

Water Requirements (optional) Cold water connection ¾" BSP male

80psi maximum inlet pressure / 20psi minimum inlet pressure

External Dimensions Width 945mm

Height 1571mm (E27T2/2)

1653mm (E27T2/2C)

Depth 762mm

Oven Internal Dimensions (each oven)

Width 695mm Height 305mm Depth 470mm Volume 0.10m3 Oven Rack Dimensions Width 660mm Depth 460mm

Nett Weight (double stack complete)

141kg

Packing Data (E27T2 ovens each)

77.8kg 0.57m3

Width 875mm Height 640mm Depth 1010mm

Packing Data (Stacking Kit) 19kg (DSK2728T - adjustable feet) 22kg (DSK2728TC - castor)

0.08m3

Width 590mm Height 840mm Depth 160mm

Supplied CKD for assembly on site

INSTALLATION CLEARANCES

Rear 25mm LH Side 25mm RH Side 25mm

CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is

Double Stacking Kits

For after market double stacking two E27T2 convection ovens DSK2728T - Double stacking kit - adjustable feet DSK2728TC - Double stacking kit - castor

MOFFAT®

Australia
www.moffat.com.au
New Zealand
www.moffat.co.nz
www.turbofanoven.com

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch
45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management SGS Standard

Designed and manufactured by




ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.TFN.S.1901





112 mm / 4%



an Ali Group Company

