turbofan®

30DSERIES E31D4/2 E31D4/2C

Technical data sheet for

E31D4 DOUBLE STACKED

Half Size Digital / Electric Convection Ovens Double Stacked on a Stainless Steel Base Stand



C

E31D4/2E31D4/2C

E31D4 ovens shall be Blue Seal electrically heated Turbofan convection ovens. The ovens shall have a one piece vitreous enamel oven chamber, stainless top and sides and safe touch vented easy clean side hinged door that offers field reversible hinging. Ovens shall have capacity for four GN1/1 pans and include a top grilling oven element and grill operating mode. The ovens shall be controlled by an electronic control having separate digital displays and adjusting knobs for time and temperature functions. The oven controls shall allow both manual and programmed operating modes and have separate control keys for selection of Grill mode, oven light function and timer operation. The units shall include a halogen oven lamp. Ovens shall be fitted with a 13A plug-in cordset. Ovens shall be double stacked using Double Stacking Kits DSK272831 (adjustable feet option) or DSK272831C (castor option). Units shall be supplied in 100% recyclable shipping packaging.

Double stack models are supplied as two individual ovens and a double stacking kit for field assembly.

E31D4/2 - Double stack with adjustable feet base stand E31D4/2C - Double stack with castor base stand

DOUBLE STACK FEATURES

- Two 4 Gastronorm GN1/1 pan capacity
- · Compact 666mm depth x 810mm width
- · Full stainless steel base stand
- · Full stainless steel oven spacer frame
- · Adjustable feet or castor models
- Guard rail for bottom oven

OVEN FEATURES (each)

- 4 Gastronorm GN1/1 pan capacity
- 80mm tray spacing
- 13A plug-in cordset fitted
- · Digital display time and temperature controls
- · Large easy view 20mm high displays
- Electronic thermostat control
- · Electronic timer with countdown or time count modes
- · Programmable for up to 20 programs
- Grill mode
- Single direction low-velocity fan
- 2.8kW heating in bake mode / 2.0kW grill elements
- Safe-Touch vented side hinged door (standard LH hinge).
 Optional RH hinge (field convertible)
- Stay-Cool door handle
- · Vitreous enamel oven chamber
- · Plug-in continuous oven door seal
- Halogen oven lamp
- 4 oven wire racks supplied



turbofan®

E31D4/2 E31D4/2C Half Size Digital / Electric Convection Ovens Double Stacked on a Stainless Steel **Base Stand**

CONSTRUCTION - OVENS Vitreous enamel fully welded oven chamber Stainless steel front, sides and top exterior Vitreous enamel oven fan baffle Removable 4 position chrome plated wire side racks Oven racks chrome plated wire (4 supplied) Stainless steel frame side hinged door 5mm thick door outer glass 5mm thick low energy loss door inner glass Full stainless steel welded door handle Stainless steel control panel Aluminized coated steel base and rear panels CONSTRUCTION - DOUBLE STACKING KIT All stainless steel construction Welded 32mm and 38mm square tube front and rear frame base stand 4 adjustable feet on E31D4/2 4 dia. 76mm swivel castors with 2 front castors dual wheel and swivel lock on E31D4/2C Stainless steel oven spacer frame Stainless steel bottom oven vent extension CONTROLS (each oven) Electronic controls with digital time and temperature display. Manual or Program modes Large 20mm high LED displays Two individual time and temperature setting control knobs 6 function keys ON/OFF kev Oven Lamp key (toggle or auto-time off mode settings) Timer Start/Stop key Broil/Grill mode quick select key Programs select key Actual temperature display key Adjustable buzzer/alarm volume Thermostat range 50-260°C Timer range from 180 minutes in countdown mode Timer range up to 999 minutes in time count mode for holding, slow cooking Over-temperature safety cut-out CLEANING


Stainless steel top and sides continuous exterior panel Vitreous enamel oven chamber

Fully removable chrome plated oven side racks

Removable porcelain enameled oven fan baffle

Easy clean door system with hinge out door inner glass (no tools required)

Removable plug-in oven door seal (no tools required)



SPECIFICATIONS Electrical Requirements (each oven) 230-240V, 50Hz, 1P+N+E, 3.1kW, 12.9A 13A cordset fitted External Dimensions 810mm Width 1611mm (E31D4/2) Height 1693mm (E31D4/2C) Depth 666mm **Oven Internal Dimensions** Width 565mm Height 425mm Depth 395mm Volume 0.09m3 **Oven Rack Dimensions** Width 540mm Depth 370mm Nett Weight (double stack complete) 126kg Packing Data (E31D4 ovens each) 68.2kg 0.45m3 Width 740mm Height 720mm 835mm Depth Packing Data (Stacking Kit) 19kg (DSK272831 - adjustable feet) 22kg (DSK272831C - castor) 0.08m3 590mm Width Height 840mm 160mm Depth Supplied CKD for assembly on site

INSTALLATION CLEARANCES

200mm Тор Rear 50mm I H Side 50mm **RH** Side 75mm For fixed installations a minimum of 500mm is required for service CLEARANCE FROM SOURCES OF HEAT A minimum distance of 300mm from the appliance sides is required

Double Stacking Kits

For after market double stacking two E31D4 convection ovens DSK272831 - Double stacking kit - adjustable feet DSK272831C - Double stacking kit - castor

Model E31D4/2 shown Model E31D4/2C dimensions: Add 31/4" / 82mm to vertical heights

30DSERIES

E31D4/2 E31D4/2C

OBLUE SEAL

blue-seal.co.uk turbofanoven.com

United Kingdom **Blue Seal Limited**

Unit 67 Gravelly Business Park Gravelly Birmingham B24 8TQ England Telephone 0121-327 5575 Facsimile 0121-327 9711 sales@blue-seal.co.uk www.blue-seal.co.uk

Australia Moffat Pty Limited

740 Springvale Road Mulgrave, Victoria 3170 Australia Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz www.moffat.co.nz







ISO9001 All Turbofan products are designed

and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

CE © Copyright Moffat Ltd UK.TFN.S.2301

an Ali Group Company

