



SINGLE PAN ELECTRIC FRYER 600mm

E60

- 22kW high performance single pan fryer
- Easy clean flat bar heating elements
- Easy clean stainless steel open pan with 10 year limited warranty
- 35L oil capacity
- 3 standard or 2 large basket capacity
- Electronic thermostat
- 32mm (1½") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



E60

Overall Construction

- · Stainless steel pan
- \cdot Bull nose welded 1.5mm 304 stainless steel
- · Splashback 1.2mm 304 stainless steel
- · Side panels 1.2mm 304 stainless steel
- · Double skin door with 0.9mm 304 stainless exterior
- \cdot Vitreous enamelled control panel
- · Hinge out counterbalanced heating elements
- · 32mm (1½") drain valve
- $\,\cdot\,63\text{mm}$ dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- · 3 standard baskets and stainless steel lid supplied standard

Controls

- · Electronic thermostat
- · Thermostat range 90-190°C
- · Large easy use control with easy view scale
- \cdot Fail-safe over-temperature safety cut-out
- \cdot Element tilt switch for heating cut-out on element lift
- · Indicator lights for power and heating
- · Safety start switch

Cleaning and Servicing

- \cdot Open stainless steel pan with hinge out elements for easy clean
- · Easy clean basket support bar
- · 32mm (1½") drain valve for effective draining
- · Easy clean stainless steel exterior
- · Access to all controls from front of unit



SINGLE PAN GAS FRYER 600mm

F60

Specifications

Production rate

40kg/hr

Pan Size

Oil capacity 35L (50lbs shortening) Width 515mm Length 390mm Oil frying depth 95mm

Baskets

3 nickel plated wire baskets 140mm W x 335mm D x 145mm H Optional 2 nickel plated wire baskets 210mm W x 335mm D x 145mm H

Elements

2 x 11kW flat bar stainless steel heating elements

Electrical requirements

22kW, 400-415Vac, 50/60hz, 3P+N+E

L1 30.5A L2 30.5A L3 30.5A

Electrical connection

41mm from RH side, 70mm from rear and 485mm from floor

Dimensions

Width 600mm Depth 812mm Height 915mm

Incl. splashback 1085mm

Nett weight

74kg

Packing data

0.7m3, 99kg

Width 670mm


Depth 900mm

Height 1255mm

Options

Adjustable feet at rear Filtamax Filtration System Extra standard baskets Extra large baskets Side splash guards Joining caps Castors

E60





MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6600 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management SGS Standard

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.SS.01.23