

BLUE SEAL EVOLUTION SERIES®

TWIN PAN ELECTRIC FRYER 600mm

E66

- 22kW high performance twin pan fryer
- Easy clean flat bar heating elements
- Easy clean stainless steel open pan with 10 year limited warranty
- 17.5L per pan oil capacity
- 2 large basket capacity
- Electronic thermostat
- 25mm (1") drain valves
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



Overall Construction

- \cdot Stainless steel pan
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- \cdot Side panels 1.2mm 304 stainless steel
- \cdot Double skin door with 0.9mm 304 stainless exterior
- \cdot Vitreous enamelled control panel
- $\boldsymbol{\cdot}$ Hinge out counterbalanced heating elements
- \cdot 25mm (1") drain valves
- \cdot 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- \cdot 2 large baskets and stainless steel lid supplied standard

Controls

- \cdot Electronic thermostats
- \cdot Thermostat range 90-190°C
- $\boldsymbol{\cdot}$ Large easy use controls with easy view scale
- $\boldsymbol{\cdot}$ Fail-safe over-temperature safety cut-outs
- $\boldsymbol{\cdot}$ Element tilt switch for heating cut-out on element lift
- \cdot Indicator lights for power and heating (per pan)
- \cdot Safety start switch

Cleaning and Servicing

- $\boldsymbol{\cdot}$ Open stainless steel pans with hinge out elements for easy clean
- Easy clean basket support bar
- \cdot 25mm (1") drain valves for effective draining
- Easy clean stainless steel exterior
- $\boldsymbol{\cdot}$ Access to all parts from front of unit

BLUE SEAL EVOLUTION SERIES®

TWIN PAN ELECTRIC FRYER 600mm

E66

Specifications

Production rate 40kg/hr

Pan Size (per pan)

Oil capacity 17.5L (24lbs shortening) per pan Width 250mm Length 390mm Oil frying depth 95mm

Baskets

2 nickel plated large wire baskets 210mm W x 335mm D x 145mm H

Elements (per pan)

1 x 11kW flat bar stainless steel heating element

Electrical requirements

| 22kW, | , 400-415Vac, 50/60Hz, 3 | 3P+N+E |
|-------|--------------------------|--------|
| L1 | 30.5A | |
| L2 | 30.5A | |
| L3 | 30.5A | |

Electrical connection 41mm from RH side, 70mm from rear and 485mm from floor

Dimensions

Width 600mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight 77kg


Packing data 0.76m3, 102kg Width 670mm

Depth 900mm Height 1255mm

Options

Adjustable feet at rear Filtamax Filtration System Extra baskets Side splash guards Joining caps Castors









moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz





Quality Management

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.SS.01.23

an Ali Group Company

