turbofan



EC40T10

Technical data sheet for

EC40T10 ON THE SK40-10A STAND

Full Size 10 Tray Touch Electric Combi Oven on a Stainless Steel Stand





FC40T10

Unit shall be a Blue Seal electrically heated Turbofan direct steam injection combination convection steam oven. The oven shall have a stainless steel oven chamber with 10 x 1/1 GN capacity, 14.5 kW power rating and a 2 speed auto-reversing direction fan. Oven door shall be vented, safe to touch and feature LED oven chamber lighting. Automatic one touch display that can be configured based on the needs of the user that provide convection, steam, and combi cooking mode selection. Oven shall be able to be bench mounted on 100mm feet or mounted on Turbofan oven stand model SK40A. Unit shall be supplied in 100% recyclable shipping packaging.

SK40-10A

Unit shall be a Blue Seal Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with 4 adjustable feet. It shall be fitted with 6 tray runners suitable for 1/1 GN pans and $600\, x\, 400$ trays. The stand shall be fully compatible with, and support, Turbofan Combi Oven EC4010 models. Unit shall be supplied in 100% recyclable shipping packaging

STANDARD FEATURES

- · Electric direct steam version
- 10 x 1/1 GN tray capacity
- 10 x 600mm x 400mm tray capacity
- 70mm tray spacing
- · Compact 777mm wide
- · 14.5kW heating power
- · 2 speed fan
- Manual cooking with three cooking modes Convection (30°C-260°C), Steam (30°C-130°C), Combi (30°C-260°C)
- Autoclima® system that automatically manages the perfect climate in the cooking chamber
- MULTILEVEL PLUS multi-level function on each shelf means doubling production capacity (patented)
- High-definition 7-inch capacitive LCD colour touch screen function configurable based on user preferences
- Programmable modes: create and save a recipe with its cooking methods in an automatic sequence (up to 15 cycles) giving each programme its own name, picture and information
- · Intelligent recognition of recipes in multilevel folders
- ICS (Interactive Cooking System), an automatic cooking system for preset recipes including their history, ingredients, cooking accessory, procedure, automatic cooking programme and picture
- · Automatic one touch cooking (ICS)
- Auto reverse (automatic inversion of the direction of the fan) for perfectly uniform cooking
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- · Core temperature probe
- Automatic cleaning system LCS (Liquid Clean System) with built-in tank and automatic dispensing
- USB connection to download HACCP data, software update and cooking programme management
- · Wi-Fi connectivity
- · Low consumption LED cooking chamber lighting
- · Self-diagnostic with smart error viewing
- Door with rear ventilation, double tempered glass front with air chamber and interior heat-reflecting glass
- · Internal glass that folds for easy cleaning
- Cooking chamber in 1mm thick AISI 304 stainless steel with fully rounded edges for best airflow and easy cleaning
- Triple action water filter cartridge and filter head included

ACCESSORIES

- · Turbofan SK40-10A oven stand
- Externally fitted hand shower
- Extraction hood





turbofan

EC40T10

EC40T10 Full Size 10 Tray Touch / Electric Combi Oven

Dimensions

777mm Width 744mm Depth Height 1097mm 104kg Weight

Packed Dimensions

Width 910mm Depth 865mm 1265mm Height 117kg Weight Volume 0.63 m³

Shelves

1/1 GN 10 Shelf Spacings 70mm

Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed

near the appliance.

Electrical requirements

400-415V, 50Hz, 3P+N+E, 14.5kW @ 400V, 22A

Water connection requirements

Water Supply

2 x R3/4 connections

Cold Water (Softened water optional)

Flow pressure 200-500 kPa

Shut off valve with back flow prevention

Water Quality

60-90 ppm total hardness рΗ > 7.5 CI-(chloride) max. 30 mg/l CI2 (free chlorine) max. 0.1 mg/l Fe (iron) max. 0.1 mg / I max. 0.2 mg/l NH2CI (monochloramine) max. 30° C cold water temperature Electrical conductivity 50 - 200 uS

- Funnel waste trap/turndish required
- 40 mm outlet
- Minimum fall/slope for waste 4°
- Drain must be outside oven perimeter

SK40-10A Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan EC40 10 tray Series Combi ovens

6 position tray runners 4 height adjustable feet

Supplied CKD for assembly on site

External Dimensions (SK40-10A Oven Stand)

Width 810mm Height 697mm Depth 650mm Weight 19kg

Packing Data (SK40-10A Oven Stand)

22kg 0.11m3

Width 830mm Height 880mm Depth 160mm

INSTALLATION CLEARANCES

Installation requirements (for precise installation instructions, please refer to the unit's installation manual).

- rear 50mm - right 50mm* - left 50mm*

* A minimum of 500mm clearance must be maintained on one of the sides for servicing.

The unit cannot be installed in a recess.

If heat sources are located near the Turbofan Combi, ensure that a minimum distance of 400mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

OBLUE SEAL

blue-seal.co.uk turbofanoven.com

United Kingdom Blue Seal Limited

Unit 67

Gravelly Business Park Gravelly

Birmingham B24 8TQ

England

Telephone 0121-327 5575 Facsimile 0121-327 9711 sales@blue-seal.co.uk www.blue-seal.co.uk


Australia Moffat Ptv Limited

740 Springvale Road Mulgrave, Victoria 3170 Australia

Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz www.moffat.co.nz





Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.





© Copyright Moffat Ltd UK.TC.01.25