# turbofan

# COMB 40TSERIES EC40T7

# Technical data sheet for **EC40T7** ON THE SK40A STAND

# Full Size 7 Tray Touch Electric Combi Oven on a Stainless Steel Stand





# EC40T7

Unit shall be a Moffat electrically heated Turbofan direct steam injection combination convection steam oven. The oven shall have a stainless steel oven chamber with 7 x 1/1 GN capacity, 12.5 kW power rating and a 2 speed auto-reversing direction fan. Oven door shall be vented, safe to touch and feature LED oven chamber lighting. Automatic one touch display that can be configured based on the needs of the user that provide convection, steam, and combi cooking mode selection. Oven shall be able to be bench mounted on 100mm feet or mounted in Turbofan oven stand model SK40A. Unit shall be supplied in 100% recyclable shipping packaging.

## SK40A

Unit shall be a Moffat Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with 4 adjustable feet. It shall be fitted with 6 tray runners suitable for 1/1 GN pans and 600 x 400 trays. The stand shall be fully compatible with, and support, Turbofan Combi Oven EC405 and EC407 models. Unit shall be supplied in 100% recyclable shipping packaging

## STANDARD FEATURES

- Electric direct steam version
- 7 x 1/1 GN tray capacity
- 7 x 600mm x 400mm tray capacity
- 70mm tray spacing
- Compact 777mm wide
- 12.5kW heating power
- 2 speed fan
- Manual cooking with three cooking modes Convection (30°C-260°C), Steam (30°C-130°C), Combi (30°C-260°C)
- Autoclima® system that automatically manages the perfect climate in the cooking chamber
- MULTILEVEL PLUS multi-level function on each shelf means doubling production capacity (patented)
- High-definition 7-inch capacitive LCD colour touch screen function configurable based on user preferences
- Programmable modes: create and save a recipe with its cooking methods in an automatic sequence (up to 15 cycles) giving each programme its own name, picture and information
- · Intelligent recognition of recipes in multilevel folders
- ICS (Interactive Cooking System), an automatic cooking system for preset recipes including their history, ingredients, cooking accessory, procedure, automatic cooking programme and picture
- · Automatic one touch cooking (ICS)
- Auto reverse (automatic inversion of the direction of the fan) for perfectly uniform cooking
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- Core temperature probe
- Automatic cleaning system LCS (Liquid Clean System) with built-in tank and automatic dispensing
- USB connection to download HACCP data, software update and cooking programme management
- Wi-Fi connectivity
- Low consumption LED cooking chamber lighting
- Self-diagnostic with smart error viewing
- Door with rear ventilation, double tempered glass front with air chamber and interior heat-reflecting glass
- · Internal glass that folds for easy cleaning
- Cooking chamber in 1mm thick AISI 304 stainless steel with fully rounded edges for best airflow and easy cleaning
- Triple action water filter cartridge and filter head included

## ACCESSORIES

- Turbofan SK40A oven stand
- Externally fitted hand shower
- Extraction hood



# turbofan

# EC40T7 Full Size 7 Tray Touch / Electric Combi Oven

Dimensions Width 777mm 744mm Depth Height 887mm 90kg Weight Packed Dimensions 910mm Width 865mm Depth Height 1050mm 102kg Weight Volume 0.51 m<sup>3</sup> Shelves

#### 7 1/1 GN Shelf Spacings 70mm

Power connection requirements Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

### Electrical requirements

400-415V, 50Hz, 3P+N+E, 12.5kW @ 400V, 18A

# Water connection requirements

Water Supply 2 x R3/4 connections Cold Water (Softened water optional) Flow pressure 200-500 kPa

Shut off valve with back flow prevention Water Quality

# total hardness

60-90 ppm pН >75 Cl-(chloride) max. 30 mg/l CI2 (free chlorine) max. 0.1 mg / I Fe (iron) max. 0.1 mg / l max. 0.2 mg /l NH2CI (monochloramine) max. 30° C cold water temperature Electrical conductivity 50 - 200 uS

### Drain

- Funnel waste trap/turndish required

- 40 mm outlet
- Minimum fall/slope for waste 4°
- Drain must be outside oven perimeter

## SK40A Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan EC40 5 tray and 7 tray Series Combi ovens 6 position tray runners 4 height adjustable feet Supplied CKD for assembly on site External Dimensions (SK40A Oven Stand) Width 810mm Height 854mm Depth 650mm Weight 19kg Packing Data (SK40A Oven Stand) 22kg 0.11m3 Width 830mm 880mm Height Depth 160mm INSTALLATION CLEARANCES Installation requirements (for precise installation instructions, please refer to the unit's installation manual). **F**0 - rea

ar	50mm
ht	50mm*
t	50mm*

- rig

- left

\* A minimum of 500mm clearance must be maintained on one of the sides for servicing.

The unit cannot be installed in a recess.

If heat sources are located near the Turbofan Combi. ensure that a minimum distance of 400mm is maintained. Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

# MOFFAT

**EC40T7** 

# moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited Rolleston

45 Illinois Drive Izone Business Hub **Rolleston 7675** Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz






Designed and manufactured by MOFFAT.

# ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection. ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd AN.TC.01.25





Ô The Spirit of Excellence



