

ELECTRIC COUNTER TILTING SKILLET



Shown with optional stand and faucet.

SPECIFICATIONS:

Shall be a CROWN Model **ECTS-12**, electrically heated counter tilting skillet, c-CSA-us and NSF Certified. The skillet shall have a one-piece covered corner, 10 gauge stainless steel pan with #4 finish exterior and polished interior. Heating shall be accomplished by electric elements cast embedded into a full 1-1/2" (38 mm) thick aluminum casting clamped to the underside of the pan for even heat distribution across the entire surface.

The skillet pan shall be mounted on side pivots to allow tilting for complete removal of contents by means of a tilting handle with heat proof knob. A tilt position device shall permit the pan to be tilted forward slightly during cooking to aid grease removal. The mounting base shall be fitted with mounting lugs for securing to counter or optional stand. The controls shall be integrally mounted in the stainless steel clad console and shall include a power switch, operating thermostat, pilot light and high temperature cut-off.

The skillet shall operate in a temperature range of 160°F to 445°F (70°C to 230°C).

Model	Capacities		
	kW	US Gal.	Litres
ECTS-12	9	12	45

OPERATION SHALL BE BY:

Electric heating elements equipped for operation on:

- 208 VAC, 1 phase, 50/60 Hz.
- 208 VAC, 3 phase, 50/60 Hz.
- 220 VAC, 1 phase, 50/60 Hz.
- 220 VAC, 3 phase, 50/60 Hz.
- 240 VAC, 1 phase, 50/60 Hz.
- 240 VAC, 3 phase, 50/60 Hz.
- 380/220 VAC, 3 phase, 4 wire, 50/60 Hz.
- 415/240 VAC, 3 phase, 4 wire, 50/60 Hz.

OPTIONS AT EXTRA COST:

- 380 VAC, 3 phase, 50/60 Hz.
- 415 VAC, 3 phase, 50/60 Hz.
- 480 VAC, 3 phase, 50/60 Hz.
- 600 VAC, 3 phase, 50/60 Hz.
- Etched gallon markings (GMS-12).
- Etched litre markings (LMS-45).
- Marine Lock. (ML-1).
- Correctional package.

ACCESSORIES:

- Steam pan insert (SPI-12).
- One piece lift-off stainless steel cover (SC-12).
- Pour strainer (PS-12).
- 18" (460 mm) high floor stand c/w sliding shelf (S-30).
- 18" (460 mm) high floor stand c/w sliding drain pan and stationary drain (SD-30).
- Single pantry faucet with 12" swing spout (SF-12).
- Double pantry faucet with 12" swing spout (DF-12).
- Single pantry faucet & bracket with 60" pot filler (SP-KF).
- Double pantry faucet & bracket with 60" pot filler (DP-KF).
- Single pantry faucet spray hose with bracket (SP-SH).
- Double pantry faucet spray hose with bracket (DP-SH).



CROWN DETAILS AND DIMENSIONS

SERVICE CONNECTIONS

- ⚡ – Electrical connection to be as specified on data plate.
- 🌡️ – COLD WATER: 3/8" O.D. tubing to faucet (OPTIONAL)
- 🔥 – HOT WATER: 3/8" O.D. tubing to faucet (OPTIONAL)

ELECTRICAL CHARACTERISTICS

MODEL	kW	PHASE	AMPS PER LINE						
			208V	220V	240V	380V	415V	480V	600V
ECTS-12	9.0	1	43.3	40.9	37.5	N/A	N/A	N/A	N/A
		3	25.0	23.6	21.7	13.7	12.5	10.8	8.7

DIMENSIONS

MODEL	CAPACITY	UNITS	A	B	C	D	E	F	G	H	J	K	L	M	N
ECTS-12	12 gallons	inches	29.25	17	4	2	24	26.5	5.5	12.5	20.75	13	10.5	34.13	7.5
	46 litres	mm	743	432	102	51	610	673	140	318	527	330	267	867	191

