



EMT24676BSPT, EMT34676BSPT

Electric Modular Deck Ovens / Prover Combinations

Product Features

- 2 & 3 Deck Ovens with 2 or 3 Baking chambers
- Tray size: 460mm x 760mm
- Stainless steel external construction
- Plate glass upward opening doors
- Each baking chamber fitted with a "Touch" control panel
- Internal height of decks is 240mm with door opening of 200mm
- Modular Prover base on wheels 12 or 18 tray capacity
- Each deck is fitted with a steam generator
- Automatic steam inlet
- · Cement baking tiles
- Internal light
- · Baking timer
- Easy installation



3EMT24676BSP

Tagliavini has a rich history of manufacturing rotating rack and deck ovens that deliver outstanding baking performance. Located in Parma, Italy, Tagliavini has been producing high-quality, high-performing baking equipment since 1934. With a clear focus on energy efficiency and reliability, Tagliavini ovens are built to last in the most demanding of baking environments, all the while delivering incredible baking results

The Tagliavini range includes single and double rack ovens in both electric and gas heated options, modular deck ovens from 2 to 24 tray capacity, Artisan deck ovens up to 24.7 sqm of baking surface and available with integrated loader options, Convection and Pizza deck ovens.

.





EMT24676BSPT, EMT34676BSPT

Electric Modular Deck Ovens/Prover Combinations

Model	External Dimensions (mm)			Internal Dimensions (mm)			Kilowatt	Number	Number	Baking Surface	Base Height
	Width (A)	Depth (B)	Height (C)	Width (A)	Depth (B)	Height (C)	(kW)	Decks	Trays	(m²)	(mm)
2EMT24676BSPT	1340	1270	1916	950	890	240	12.5	2	4	1.7	1000
3EMT24676BSPT	1340	1270	2105	950	890	240	18.5	3	6	2.55	800
2EMT34676BSPT	1810	1270	1916	1420	890	240	17.5	2	6	2.52	1000
3EMT34676BSPT	1810	1270	2105	1420	890	240	26	3	9	3.78	800

Electrical Requirements:

400-415V, 3P+N+E, 50Hz

Additional Information

Tagliavini Modular Deck ovens require one wall mounted isolator for each deck. Ovens come fully assembled (modular component form optional). Depth excludes protrusions i.e. door handles, flue handles. Overall height excludes final water inlet fittings on the top of the oven

moffat.com.au moffat.co.nz

Australia moffat.com.au

monat.com.au

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales

Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia

Telephone +613-9518 3888 vsales@moffat.com.au

Queensland

Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

This specification sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

© Copyright Moffat Ltd AN.T.1021

an Ali Group Company

