

Technical data sheet for

FAST FRI SINGLE PAN GAS FRYER 450mm

FN8120G



- High performance single pan fryer
- Patented infra-red burner system
- Easy clean stainless steel open pan with 10 year limited warranty
- 20L oil capacity
- Large capacity cool zone
- 32mm (1 1/4") drain valve
- Stainless steel exterior
- Easy service
- Fully modular
- Low back model (FNL) available

Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.5mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- 32mm (1¹/₄") drain valve
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet
- 2 baskets and stainless steel lid supplied standard

Controls

- Direct action thermostat reacts to + or 1.0°C
- Thermostat range 145 195°C
- Over-temperature safety cut-out
- Millivolt gas valve system (no electrical supply)
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

Cleaning and Servicing

- Open stainless steel pan for easy clean
- Easy clean basket support bar
- + 32mm (1 $^{\prime}\textsc{/2})$ drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

Technical data sheet for FAST FRI SINGLE PAN GAS FRYER 450mm



Specifications Production rate 31kg/hr Pan Size Oil capacity 20L (37lbs shortening) Width 365mm Length 380mm Oil frying depth 95mm Baskets 2 chrome plated wire baskets 140mm W x 335mm D x 145mm H Stainless steel perforated basket support plate Burners Burners 2 x 45MJ/hr infra-red burners Gas Power 90MJ/hr, 25kW Gas connection R ³/4 (BSP) male 300mm from RH side, 35mm from rear, and 135mm from floor and 125mm from floor Optional rear connection (refer specification drawing) All units incorporate Natural and LP gas regulator DIMENSIONS Width 450mm Depth 805mm Height 915mm Incl. splashback 1130mm Incl. low back 1085mm NETT WEIGHT 81kg PACKING DATA 0.54m3, 122kg Width 870mm Depth 495mm Height 1255mm GAS TYPES Available in Natural gas and LP gas Please specify when ordering Units supplied complete with gas type conver-sion kits Other gas types on request OPTIONS AT EXTRA COST Waldorf Filtamax filtration system Fish plates Extra baskets Side splash guards Joining caps Castors Plinth mounting

FN8120G 805 92 450 LOW BACK OPTION OPTIONAL GAS ENTRY 1130 915 525 GAS 1085 ENTRY 50 Н 124 151 189 36 85 354 540



MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand

moffat.co.nz Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz





Quality Management SGS Standard



Cert. No. 6882

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.W8.08/19

an Ali Group Company

