



MX20AT7R Reach-in Blast Chiller / Freezer

Standard Features

- · Free standing and self-contained unit on legs
- 7" ergonomic touch screen with large keys for ease of use
- User friendly operation with easy to use functions:
 - Hard or soft chill / hard or soft freeze mode
 - Easy switch to probe or timer mode
 - Self Adaptive intelligent chilling mode
- Auxiliary functions: ice cream hardening, ventilated drying, multiple timers, customisable multiple phases, raw fish sanitation
- 40 programmable cycles with favourites key shortcuts to • last 9 programs used
- Eco-friendly R455A refrigerant gas model
- · Refrigerant evaporator with double air flow
- · Removable and adjustable shelf runners able to accept gastronorm pans or euro standard 600mm x 400mm bakery trays
- Adjustable shelf runner height 5 x 64mm or • 9 x 32mm spacing
- Supplied with 5 pairs of shelf runners .
- Pre-chilling cycle key to maximise efficiency
- Automatic hold mode after each cycle •
- Manual defrosting with automatic control of time
- 3 point core temperature probe
- Timer mode or continuous run •
- Integrated door latch to aerate cabinet when not in use • • Right hinge door model - left hinge door available upon
- request Automatic fan stop when opening the door •
- External and internal finish made of 304 stainless steel
- Heated door frame to reduce condensation ٠
- ٠ Injected polyurethane foam insulation - 60mm thick
- 150mm high stainless steel adjustable feet to 180mm


Please refer to Moffat price list for options and accessories

Technical data

| Tray capacity | 5 x 1/1GN trays or 5 x Euro 600mm x 400mm trays | |
|---|--|--|
| Tray clearance | 64mm | |
| External dimensions | W 770mm x D 790mm x H 945mm | |
| Load capacity | 20kg chill / 10kg freeze* | |
| Electrical connections | 1P+N+E, 230-240V, 50/60Hz, 10A, 1.6kW | |
| Nett weight | 125kg | |
| Air-cooled condensing unit - Refrigerant type R455A | | |
| Ambient temperature requirement +15°C — +32°C | | |

* Note - Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used

| Australia | New Zealand |
|--------------------------|--------------------------|
| moffat.com.au | moffat.co.nz |
| Moffat Pty Limited | Moffat Limited |
| 740 Springvale Road | 45 Illinois Drive |
| Mulgrave | Izone Business Hub |
| Victoria 3170 | Rolleston 7675 |
| Australia | New Zealand |
| Telephone +613-9518 3888 | Telephone +64 3-983 6600 |
| Facsimile +613-9518 3833 | Facsimile +64 3-983 6660 |
| vsales@moffat.com.au | sales@moffat.co.nz |



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice. © Copyright Moffat Ltd AN-FRI-S-2501




an Ali Group Company

The Spirit of Excellence







(A) Electrical power supply (CU) Useful (MIN) Minimum

