

MX55AT7R Reach-in Blast Chiller / Freezer

Standard Features

- Free standing and self-contained unit on legs
- 7" ergonomic touch screen with large keys for ease of use
- User friendly operation with easy to use functions:
 - Hard or soft chill / hard or soft freeze mode
 - Easy switch to probe or timer mode
 - Self Adaptive intelligent chilling mode
- Auxiliary functions: ice cream hardening, ventilated drying, multiple timers, customisable multiple phases, raw fish sanitation
- 40 programmable cycles with favourites key – shortcuts to last 9 programs used
- Eco-friendly R455A refrigerant gas model
- Refrigerant evaporator with double air flow
- Removable and adjustable shelf runners able to accept gastronorm pans or euro standard 600mm x 400mm bakery trays.
- Adjustable shelf runner height 15 x 70mm or 35 x 35mm spacing
- Supplied with 15 pairs of shelf runners
- Pre-chilling cycle key to maximise efficiency
- Automatic hold mode after each cycle
- Manual defrosting with automatic control of time
- 3 point core temperature probe
- Right hinge door model - left hinge door available upon request
- Timer mode or continuous run
- Integrated door latch to aerate cabinet when not in use
- Automatic fan stop when opening the door
- External and internal finish made of 304 stainless steel
- Heated door frame to reduce condensation
- Injected polyurethane foam insulation - 60mm thick
- 150mm high stainless steel adjustable feet to 180mm

Please refer to Moffat price list for options and accessories

Technical data

Tray capacity	15 x 1/1 GN trays
Tray clearance	70mm
External dimensions	W 770mm x D 790mm x H 1925mm
Load capacity	55kg chill / 20kg freeze*
Electrical connections	1P+N+E, 230-240V, 50/60Hz, 15A, 2.48kW
Nett weight	160kg
Waste	Provide for a water runoff with trap
Air-cooled condensing unit - Refrigerant type R455A	
Ambient temperature requirement +15°C — +32°C	

* Note – Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used

Australia
moffat.com.au


Moffat Pty Limited
740 Springvale Road
Mulgrave
Victoria 3170
Australia
Telephone +613-9518 3888
Facsimile +613-9518 3833
vsales@moffat.com.au

New Zealand
moffat.co.nz


Moffat Limited
45 Illinois Drive
Izone Business Hub
Rolleston 7675
New Zealand
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz



Dimensions



- (A) Electrical power supply
(B) De-icing water runoff
(SG) Without housed unit
(D) Liquid line 3/8"
(D') Suction line 5/8"
(CU) Useful
(MIN) Minimum



Disclaimer: All unit capacities are based on subjective testing. Moffat accepts no liability for production values.
In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
AN-FRI-S-2501



an Ali Group Company



The Spirit of Excellence