## **BLUE SEAL EVOLUTION SERIES®**

# Technical data sheet for SINGLE PAN GAS PASTA COOKER 450mm

- High performance single pan pasta cooker
- Patented infra-red burner system
- Easy clean 316 grade stainless steel open pan
- 40L water capacity
- Integrated water fill and starch skimming water faucet
- Six stainless steel pasta baskets supplied
- Hinged basket drain stand
- Safety cut-out thermostat for empty pan/water boil out
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



G47

#### **Overall Construction**

- Pan 1.5mm 316 stainless steel
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- 25mm (1") skimming overflow and pan drains drain valve
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjustable feet
- 6 stainless steel baskets with moulded handles
- 304 stainless steel wire basket support grid in pan

#### Controls

- Large easy to use knob heat resistant reinforced
- Variable high boil to standby simmer burner control
- Fine adjustment water faucet for pan filling and water refreshing/ starch skimming
- Pan protection safety cut-out thermostat
- Millivolt gas valve system (no electrical supply)
- Flame failure protection on pilot
- Piezo ignition to standing pilot burner

#### **Cleaning and Servicing**

- Open stainless steel pan for easy clean
- Hinged basket drain stand
- Removable basket support grid
- 25mm (1") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

## Technical data sheet for SINGLE PAN GAS PASTA COOKER 450mm

#### Specifications

Pan Size Water capacity 40L Width 365mm Length 405mm Basket immersion depth 165mm

#### Baskets

6 stainless steel perforated baskets with moulded plastic handles 125mm x 165mm x 180mm deep Stainless steel wire basket support grid

Burners 1 x infra-red burner

**Gas Power** 13.5kW, 46,000 Btu/hr

Gas Connection R <sup>3</sup>/4 (BSP) male. All units supplied with Natural and LP gas regulator

#### Water Connection

Cold water connection 50mm from left hand side, 556mm from rear and 140mm from floor R<sup>1</sup>/<sub>2</sub> (BSP) male

#### **Drain Connection**

Drain must be connected to system suitable for boiling water discharge 1" BSP Male connection 118mm from left hand side, 470mm from rear, and 165mm from floor

#### Dimensions

Width 450mm Depth 812mm Height 915mm Incl. splashback 1085mm

#### Nett weight 82kg

Packing data


0.54m3, 124kg Width 870mm Depth 495mm Height 1255mm


#### Gas types


Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

#### Options

Rectangular baskets 320mm x 165mm Side splash guards Joining caps







### **OBLUE SERL**

www.blue-seal.co.uk www.bluesealevolution.com

#### **United Kingdom**

Blue Seal Limited Unit 67 Gravelly Business Park Gravelly Birmingham B24 8TQ England Telephone 0121-327 5575 Facsimile 0121-327 9711 Email sales@blue-seal.co.uk

#### Australia

Moffat Pty Limited 740 Springvale Rd Mulgrave Victoria 3170 Australia Telephone 03-9518 3888 Facsimile 03-9518 3833 Email vsales@moffat.com.au

#### New Zealand

Moffat Limited Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz



### Designed and manufactured by

### MOFFAT

IS09001 All Blue Seal products are designed and manufactured by Moffat using the internationally recognised IS09001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd Motfæs⊭.≴01&01/ 1357



## **BLUE SEAL EVOLUTION SERIES®**