GM-R COMPACT UNDERCOUNTER POLISH-FREE COMPATIBLE GLASSWASHER





STANDARD FEATURES

1, 2 and 3 minute cycles

Wash capacity of up to 960 glasses per hour

Polish-free glasswashing compatible (add BA14-DW14)

Compatible with 365mm to 450mm racks

Touchscreen controls providing advanced customisation

0.3HP soft start wash pump

Dual chemical pumps

Assured rinse c/w break tank and booster pump

Hands-free drainage system with sump and drain pump

Stainless steel wash and drain filter basket

Adjustable tilting rack slide

Independent wash and rinse arms

Uprateable power for rapid rinse recovery (1p/25A option)

Heavy-duty stainless steel construction

1x 450mm dish rack (600 70081)

1x 450mm cup rack (600 70080)

1x cutlery container (C660503)

1x quick connection kit (all hoses and 1p/15A plugset)

SPECIFICATIONS

A - Hot Water	
Temperature	65°C*
Connection	3/4" male, hose supplied
Pressure	100-350kPa
Flow	10L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.4L per cycle


D - Drainage


Drain pump flexi-hose 25mm

C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	2.75
Single phase	230-240	50	25	5.25
Three phase	400-415	50	15	7.50


Isolating switch must be within 1m of, and not directly behind, the machine Refer to operator manual for installation instructions

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without





Dimensions



Packed

Width (mm)	500	560
Depth (mm)	600	650
Height (mm)	780	915
Weight (kg)	47	57
Volume (m3)		0.33
Water Quality	Min	Max
рН	7	8
TDS	1	135
CI-		100
SO4		400
Fe		0.1
1 0		0.1
Mn		0.1

Machine

*Suitable for connection to cold water supply. To minimise recovery time between cycles it is recommended that a 1p/25A or 3/15A power supply is used in conjunction with cold inlet water.









an Ali Group Company

