

Technical data sheet for ELECTRIC GRIDDLE 600mm

GP8600E-B, GP8600E-CB, GP8600E-LS



Overall Construction

Griddle

- 20mm thick machined top plates standard
- Optional ribbed plate sections
- Optional mirror finish hard chrome plates
- 2.5mm thick 304 stainless steel splash guards sides and rear
- 2.0mm thick grease channel
- Single temperature control zone
- Welded hob surround with 1.5mm 304 stainless steel bull nose
- Splashback and side panels 1.2mm 304 stainless steel
- Front panels 0.9mm 304 stainless steel
- Stainless steel grease drawer
- Overlapping finish at front and rear of plate for easy clean
- BENCH MOUNT (SUPPLIED AS -B MODEL)
- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet
- Adjustable height 80mm 105mm

CABINET BASE (SUPPLIED AS -CB MODEL)

- Fully modular for match suite finish
- Double skin 0.9mm 304 stainless steel interior and exterior
- Optional GN 1/14 position racking kit
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjustable feet

LEG STAND (SUPPLIED AS -LS MODEL)

- Fully modular for matched suite finish
- Framed top for connection to Griddle
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjustable feet
- Fully modular framed stand shelf with 0.9mm 304 stainless steel finish
- Suitable for rear or through shelf gas connection to Griddle
- Quick assembly design (no tools required)

- Heavy-duty thermostatic electric griddle
- 20mm thick griddle plate
- Ribbed plate options
- Chromed mirror plate options
- Top weld sealed plates
- 7.2kW heating elements
- 3 models of base unit
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular
- Low back models (GPL) available

Controls

- 50-300°C thermostats
- Single temperature control zone
- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob
- Indicator lights for power and heating

Cleaning and Servicing


- All models with easy clean stainless steel external finish
- Plate is finished front and rear with overlap construction to remove cleaning traps
- Control service through front of unit

Technical data sheet for **ELECTRIC GRIDDLE 600mm**




Specifications Elements 3 x 2.4kW stainless steel sheathed heating elements Electrical requirements 7.2kW 230-240Vac, 50/60Hz, 1P+N+E, 30A Plate Cooking surface 592mm x 530mm, 3138cm2 Electrical connection 130mm from RH side, 32mm from rear, and 740mm from floor DIMENSIONS Bench models Width 600mm Depth 805mm Height 315mm Incl. splashback 530mm Incl. low back 370mm All models (excluding Bench model) Width 600mm Depth 805mm Height 915mm Incl. splashback 1130mm Incl. low back 970mm NETT WEIGHT Bench and Leg Stand models 118kg Cabinet Base models 120kg PACKING DATA Bench models 0.37m3, 170kg Width 645mm Depth 870mm Height 665mm All models (excluding Bench model) 0.70m3, 172kg Width 645mm Durate 675mm Depth 870mm Height 1255mm OPTIONS AT EXTRA COST Joining caps Castors Plinth mounting Ribbed plate options Chromed plate options













469

PLAN



130



South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Telephone +617-3630 8600

Western Australia

New Zealand

moffat.co.nz

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz Auckland

Telephone +64 9-574 3150





In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.W8.08/19

an Ali Group Company



MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

Queensland

qldsales@moffat.com.au

Telephone +618-9413 2400 wasales@moffat.com.au

Moffat Limited

sales@moffat.co.nz