

# INDUCTION COOKTOP 900mm

## - ROUND INDUCTION ZONE

IN514R3-B, IN514R3-LS, IN514R3-CB, IN514R5-B, IN514R5-LS, IN514R5-CB

- Heavy-duty construction
- Four 270mm .dia round induction zones
- 3.5kW or 5kW heating per zone
- Automatic pan detection switches induction zone off when pan removed
- 3 models of base unit
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular

#### Induction Zone Options

R3 - 3.5kW round induction R5 - 5kW round induction

#### **Overall Construction**

#### Cooktop

- Welded hob with 2.0mm stainless steel hob top
- Splashback and side panels 1.2mm stainless steel
- Front panels 0.9mm stainless steel
- 6mm thick ceramic glass cooking surface

#### Bench mount (supplied as - B model)

- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet
- Adjustable height 80mm 105mm

#### Leg stand (supplied as - LS model)

- Fully modular for matched suite finish
- Framed top for connection to Cooktop
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with two adjustable feet at front and two rollers at rear
- Fully modular framed stand shelf with 0.9mm 304 stainless steel finish
- Quick assembly design

# Cabinet base (supplied as - CB model)

- Fully modular for match suite finish
- Double skin 0.9mm 304 stainless steel interior and exterior
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with two adjustable feet at front and two rollers at rear



#### Controls

- Large easy use control knob
- Infinitely variable power controls for each induction zone
- Heating ON indicator lights (green) including pan detection indication
- Error mode indicator light (green)

## Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Fully sealed cooking surface
- Removable full stainless steel air intake filters (induction cooling)
- Front service access



# INDUCTION COOKTOP 900mm

# - ROUND INDUCTION ZONE

IN514R3-B, IN514R3-LS, IN514R3-CB, IN514R5-B, IN514R5-LS, IN514R5-CB

#### **Specifications**

#### Cooktop

4 x 3.5kW induction zones 4 x 5.0kW induction zones Ø 270mm induction zones

#### Electrical requirements

IN514R3

14kW, 400-415V, 50/60Hz, 3P+E 20A / phase IN514R5 20kW, 400-415V, 50/60Hz, 3P+E 28A / phase

#### **Dimensions**

Bench model Width 900mm Depth 812mm Height 355mm

Incl. splashback 525mm

All models (excluding Bench model) Width 900mm

Depth 812mm Height 915mm

Incl. splashback 1085mm

#### Nett weight

105kg

#### Packing data


1.03m3, 157kg 945mm Width Depth 865mm Height 1255mm


#### Options

Castors


Plinth mounting


#### IN514-B







#### IN514-LS





#### IN514-CB





#### IN514R3, IN514R5



## •BLUE ==EAL

www.blue-seal.co.uk

United Kingdon blue-seal.co.uk

# Blue Seal Limited

Unit 67 Gravelly Business Park Gravelly Birmingham B24 8TQ

England Telephone 0121-327 5575 Facsimile 0121-327 9711 sales@blue-seal.co.uk

#### Australia moffat.com.au

# Moffat Pty Limited

740 Springvale Road Mulgrave Victoria 3170 Australia Telephone +613-9518 3888 Facsimile +613-9518 3833

vsales@moffat.com.au

New Zealand moffat.co.nz

#### Moffat Limited

45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

#### International moffat.com

international@moffat.co.nz



ISO9001 Quality Management

Designed and manucatured by

# **MOFFAT**

#### ISO9001

All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.



Copyright Moffat Ltd. UK.BS.01.23



