

MFN Series Modular Nugget Ice makers – up to 305kg

MFN S 57 AS OX Nugget ice – 1g – Ø11mm x H 13mm



Nugget ice
1g – Ø 11mm x H 13mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Maximum production rate 305kg/day
- Head only ice maker: requires a separate storage bin to store the ice produced
- XSafe - Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Air cooled version
- Hermetic compressor
- Stainless steel auger and freezing cylinder (evaporator)
- Plug-and-work technology
- Water in / ice out concept limits excess energy, water and time wastage
- Simple, reliable electromechanic controls
- External indicator lights to show operation status and maintenance alert
- Double protection – electronic rotation sensor & drive coupling

- Low-water sensor protection
- Stainless steel finish, top cover in PS plastic with removable panels for ease of maintenance
- Includes removable air filter, water and drain hose


Recommended storage bins

- NB 193 with CBT22 EFCD cover – 129kg storage capacity
- NB 393 with CBT30 EFSD cover – 178kg storage capacity
- NB 530 with CBT30 EFSD cover – 243kg storage capacity
- NB 948 with CBT48 FMCD cover – 406kg storage capacity
- UBH 1100 – Upright storage bin – 553kg capacity
- UBH 1600 – Upright storage bin – 812kg capacity
- SIS 300 – Ice shuttle storage system – 137 + 73kg capacity
- SIS 700 – Ice shuttle storage system – 318 + 73kg capacity



MFN Series Modular Nugget Ice makers – up to 305kg

MFN S 57 AS OX



moffat.com.au

Australia
Moffat Pty Limited
Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
350	305	235

Dimensions

Width: 538mm
Depth: 663mm
Height: 794mm
Nett weight: 94kg
Packed weight: 103kg

Water consumption

Air cooled version: 11.1 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1300W,
10A cordset supplied
No. Circuit wire: 3
Compressor: 3600W
Energy consumption: 12.6kW/24hr

Refrigerant type

R404a

Installation distance from wall

Rear 100mm
Side 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø7/8"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.2301