

## MF Series Modular Flake Ice Maker – up to 193kg

### MF 36 AS OX Flake ice



Flake ice



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.


- Up to 193kg daily production rate
- Head only ice maker: requires a separate storage bin to store the ice produced\*
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- XSafe - Natural Sanitation System
- Air cooled version
- Hermetic compressor
- Stainless steel auger and freezing cylinder (evaporator)
- Simple, reliable electromechanic controls
- Double protection – electronic rotation sensor & drive coupling
- Low-water sensor protection
- Stainless steel finish, top cover in PS plastic with removable panels for ease of maintenance
- Includes removable water and drain hose

#### Recommended Storage Bins

- NB 193 with CBT 22 EFSD cover – 129kg storage capacity
- NB 393 with CBT 30 EFSD cover – 181kg storage capacity
- NB 530 with CBT 30 EFSD cover – 243kg storage capacity

## MF Series Modular Flake Ice Maker – up to 193kg

### MF 36 AS OX



moffat.com.au

**Australia**  
Moffat Pty Limited  
Victoria/Tasmania  
740 Springvale Road  
Mulgrave, Victoria 3170  
Telephone 03-9518 3888  
Facsimile 03-9518 3833  
vsales@moffat.com.au

**New South Wales**  
Telephone 02-8833 4111  
nswsales@moffat.com.au

**South Australia**  
Telephone 03-9518 3888  
vsales@moffat.com.au

**Queensland**  
Telephone 07-3630 8600  
qldsales@moffat.com.au

**Western Australia**  
Telephone 08-9413 2400  
wasales@moffat.com.au

#### Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
205	193	155

#### Dimensions

Width:	563mm
Depth:	536mm
Height:	531mm
Nett weight:	49kg
Packed weight:	56kg

#### Water consumption

Air cooled version: 6.7 litres per hour

#### Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 750W,  
10A cordset supplied

No. Circuit wire: 3  
Compressor: 2970W

Energy consumption: 17.5kW/24hr

#### Refrigerant type

R134a

#### Installation distance from wall

Rear	100mm
Sides	150mm

Operating requirement air temperature 10-43°C

#### Water connection requirements

Inlet connection:	R 3/4"
Cold water:	5-38°C
Pressure:	100-500kPa
Water outlet connection:	Ø3/4"

#### Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd  
AU.SM.2301