

MF Series Modular Flake Ice Makers – up to 1070kg

MF 66 AS OX Superflake ice



Superflake ice



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.


- Up to 1070kg daily production rate
- Head only ice maker: requires a separate storage bin to store the ice produced
- XSafe - Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Air cooled version
- Hermetic compressor
- Stainless steel auger and freezing cylinder (evaporator)
- Simple, reliable electromechanic controls
- Double protection – electronic rotation sensor & drive coupling
- Low-water sensor protection
- Stainless steel finish, top cover in PS plastic with removable panels for ease of maintenance
- Includes removable air filter, water and drain hose

Recommended Storage Bins

- UBH 1100 – Upright storage bin – 553kg capacity
- UBH 1600 Upright storage bin – 812kg storage capacity
- SIS 1350 – Ice shuttle storage system – 613kg + 73kg +73kg capacity
- SIS 700 – Ice shuttle storage system – 318kg + 73kg capacity

MF Series Modular Flake Ice Makers – up to 1070kg

MF 66 AS OX



moffat.com.au

Australia
Moffat Pty Limited
Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
1150	1070	870

Dimensions

Width: 1064mm
Depth: 697mm
Height: 860mm
Nett weight: 179kg
Packed weight: 198kg

Water consumption

Air cooled version: 36.3 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 3900W, 16A
No. Circuit wire: 5
Compressor: 3135W
Energy consumption: 80kW/24hr

Refrigerant type

R452a

Installation distance from wall

Rear 150mm
Sides 150mm
Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø7/8"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.2301