

## MF Series Modular Flake Ice Maker – up to 1150kg

### MF 68 Split OX Superflake ice



Superflake ice



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 1150kg daily production rate
- Split unit supplied with evaporator only – requires to be connected to remote condensing unit or central cooling system (low temperature)
- Head only ice maker: requires a separate storage bin to store the ice produced
- XSafe - Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Stainless steel auger and freezing cylinder (evaporator)
- Simple, reliable electromechanic controls
- Double protection – electronic rotation sensor & drive coupling
- Low-water sensor protection
- Stainless steel finish, top cover in PS plastic with removable panels for ease of maintenance
- Includes removable air filter, water and drain hose

#### Condenser options


- UR – Condensing unit (ambient temperature max +32°C)
- UR – Condensing unit (ambient temperature max +43°C)

#### Recommended Storage Bins

- NB 948 with CBT 48 FMCD cover – 406kg storage capacity
- UBH 1100 – Upright storage bin – 553kg storage capacity
- SIS 1350 – Ice shuttle storage system – 613 + 73 + 73kg storage capacity

### MF Series Modular Flake Ice Maker – up to 1150kg

#### MF 68 Split OX



moffat.com.au

Australia  
Moffat Pty Limited  
Victoria/Tasmania  
740 Springvale Road  
Mulgrave, Victoria 3170  
Telephone 03-9518 3888  
Facsimile 03-9518 3833  
vsales@moffat.com.au

New South Wales  
Telephone 02-8833 4111  
nswsales@moffat.com.au

South Australia  
Telephone 03-9518 3888  
vsales@moffat.com.au

Queensland  
Telephone 07-3630 8600  
qldsales@moffat.com.au

Western Australia  
Telephone 08-9413 2400  
wasales@moffat.com.au

#### Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
1150	1150	1020

#### Dimensions

Width: 538mm  
Depth: 663mm  
Height: 794mm  
Nett weight: 98kg  
Packed weight: 107kg

#### Water consumption

Air cooled version: 42.5 litres per hour

#### Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 290W,  
15A cordset supplied  
No. Circuit wire: 3  
Compressor: 4600W  
Energy consumption: 7kW/24hr

#### Refrigerant type

R404a

#### Installation distance from wall

Rear 100mm  
Sides 100mm

Operating requirement air temperature 10-43°C

#### Water connection requirements

Inlet connection: R 3/4"  
Cold water: 5-38°C  
Pressure: 100-500kPa  
Water outlet connection: Ø3/4"

#### Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd  
AU.SM.2201