



MX15-5AEM Reach-in Blast Chiller / Freezer

Standard Features

- Free standing unit on legs
- Economy unit
- Removable and adjustable shelf runners able to accept Gastronorm pans or Euro standard 600mm x 400mm bakery trays.
- Temperature display in °C.
- Automatic preservation mode at the end of cycle.
- Defrost feature removes ice from evaporator.
- R404A refrigerant CFC free.
- Self-closing door magnetically seals. Door remains open past 90°C for convenient loading and unloading.
- Internal coved corners, removable door gasket.
- Water protection index rating IP459.
- Adjustable legs for levelling.
- Electro mechanical controls.




Please refer to Moffat price list for options and accessories

Technical data

Tray capacity	3 x 1/1GN trays or 3 x Euro 600mm x 400mm trays	
Tray clearance	70mm	
External dimensions	W 770mm x D 790mm x H 955mm	
Load capacity	Blast Chilling +70°C to +3°C 15kg* Blast Freezing +70°C to -18°C 5kg*	
Electrical connections	1P+N+E, 230-240V, 50Hz, 9.5kW	
Nett weight	110kg	
Air-cooled condensing unit - Refrigerant type R452A		

Ambient temperature requirement +15°C - +32°C


Dimensions



(M1) MX15-5AEM

(A) Electrical supply

(B) De-icing waste



Australia moffat.com.au	New Zealand moffat.co.nz
Moffat Pty Limited	Moffat Limited
740 Springvale Road	45 Illinois Drive
Mulgrave	Izone Business Hub
Victoria 3170	Rolleston 7675
Australia	New Zealand
Telephone +613-9518 3888	Telephone +64 3-983 6600
Facsimile +613-9518 3833	Facsimile +64 3-983 6660

Disclaimer: All unit capacities are based on subjective testing. Moffat accepts no liability for production values. In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

sales@moffat.co.nz

© Copyright Moffat Ltd AN-FRI-S-2101

vsales@moffat.com.au





^{*} Note – Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used