

NXW Series Modular Dice Ice Machines – up to 190kg

NXW 457 AS Dice cube 10g, 22mm x 22mm x 22mm

NXWH 457 AS Half dice cube 6g, 10mm x 22mm x 28mm



Dice cube 10 g
W 22 x D 22 x H 22 mm



Half dice cube 6 g
W 10 x D 22 x H 28 mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.


- Up to 190kg daily production rate
- Head only ice maker - requires a separate storage bin to store the ice produced
- Air cooled version
- XSafe - Natural Sanitation System
- EcoX - Hydrocarbon R290 refrigerant gas
- Vertical evaporator
- Hinged front panel
- Tools free removal of internal parts (water sump, distribution tube, pump etc.)
- Easy internal cleaning
- Remote service support capability with X Wave app
- Delayed automatic start
- Automatic cleaning cycle
- Includes air filter, water and drain hose
- Double stack option available

Recommended storage bins

- NB 393 – 178kg storage capacity
- NB 530 – 243kg storage capacity

NXW Series Modular Dice Ice Machines – up to 190kg

NXW 457 AS, NXWH 457 AS



MOFFAT
moffat.com.au

Australia
Moffat Pty Limited
Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production kg per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NXW 457 AS OX	200	190	150
NXWH 457 AS OX	200	190	150

Dimensions

Width:	767mm
Depth:	636mm
Height:	600mm
Nett weight:	70kg
Packed weight:	85kg

Water consumption

Air cooled version:

NXW 457 AS OX: 8.8 litres per hour

NXW H 457 AS OX: 8 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 785W,
10A cordset supplied

No. Circuit wire: 3

Compressor: 1995W

Energy consumption:

NXW 457 AS OX: 18.2kW/24hr*

NXWH 457 AS OX: 17.8kW/24hr*

* Based on 32°C ambient / 21°C water temperature conditions

Refrigerant type

R290

Installation distance from wall

Rear 100mm

Top 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4"

Cold water: 5-38°C

Pressure: 100-500kPa

Water outlet connection: Ø 20mm

Operating requirements

	Minimum	Maximum
Air temperature	10	40
Water temperature	5	35
Water pressure	1 bar / 14psi / 100kPa	5 bar / 70psi / 500kPa

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.2609