



Technical data sheet for

## **P85M8** DOUBLE STACKED

Full Size 8 Tray Manual / Electric Prover/Holding Cabinet Double Stacked





### P85M8/2

P85M8 units shall be Moffat electrically heated Turbofan Prover and Holding Cabinets. The prover and holding cabinets shall have double skin construction with stainless steel interior and exterior sides, front and top. Doors shall be side hinged and field reversible. Units shall have capacity for 8 18' x 29' trays, or 8 18" x 29" trays with optional 18" rack set. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinets shall be controlled by a mechanical thermostat and humidity via a control of the water tank, thermometers shall indicate the cabinet temperature. Prover and Holding Cabinets shall be fitted with 10A cordsets. The prover and holding cabinets shall be double stacked using Double Stacking Kit DSKP85. Units shall be supplied in 100% recyclable shipping packaging.

Double stacked models are supplied as two individual prover and holding cabinets and a double stacking kit for field assembly.

# STANDARD FEATURES DOUBLE STACKED

- Two 8 tray capacity
- 910mm width
- Full stainless steel spacer frame

#### PROVER/HOLDING CABINET (each)

- Dual function Prover and Holding Cabinet
- 8 406mm x 736mm / 16" x 29" tray capacity
- 76mm tray spacing
- 10A cordset fitted
- Full double skin construction
- Auto water fill system with optional integrated water filter kit
- Continuous door seal
- Side hinged door (standard LH hinge). Optional RH hinge (field convertible)
- Off / Proof / Hold mode selection
- Low velocity circulation fan system
- Mechanical thermostat
- Humidity level control
- Dual halogen cabinet interior lamps
- Cabinet temperature display thermometer

#### OPTIONS

• 457mm x 762mm / 18" x 30" tray rack set for prover

## ACCESSORIES

- Optional M236060 Core Temperature Probe Kit
- Optional 3M Cuno water filter kit complete with cartridge and connection fittings (Installs in pre-fitted rear housing of cabinet for flush rear installation)





## **PSERIES**

P85M8/2

## P85M8/2 Full Size Manual / Electric Prover/Holding Cabinet

CONSTRUCTION- PROVERS

304 stainless steel interior cabinet

Stainless steel front, sides and top exterior

Stainless steel interior side racks

Stainless steel frame side hinged door

5mm thick door glass

Stainless steel control panel

Aluminised coated steel base and rear panels

CONSTRUCTION - DOUBLE STACKING KIT

All stainless steel construction Stainless steel spacer frame

CONTROLS (each prover)

Off / Proof / Holding mode selector switch.

Mechanical thermostat 20-85°C

Air heating ON control panel indicator

Humidity level control

Humidity tank ON control panel indicator

Cabinet temperature thermometer

Auto-fill water system standard

#### CLEANING

Stainless steel top and side exterior panels

Stainless steel interior chamber

Easy access to all interior surfaces

Fully removable stainless steel rack support

Removable humidity water tank (no tools)

#### **SPECIFICATIONS**

Electrical Requirements (each prover)

230-240V, 50Hz, 1.5kW, 1 phase, 6.2A

10A cordset fitted

Water Requirements (optional)

Cold water connection 3/4" BSP male

80psi maximum inlet pressure / 20psi minimum inlet pressure

External Dimensions

Width 910mm 1789mm Height Depth 880mm

Prover Internal Dimensions (each prover)

Width 465mm 730mm Height 795mm Denth Volume  $0.27m^{3}$ 

Nett Weight (double stack complete)

Packing Data (P85M8 provers each)

133kg 1.05m<sup>2</sup>

950mm Width 1070mm Height 1020mm Depth

Packing Data (Stacking Kit)

7kg

0.13m<sup>3</sup>

Width 770mm 970mm Height 170mm Depth

## **Double Stacking Kits**

For after market double stacking two P85M 8 prover/holding cabinets

DSKP85 - Double stacking kit

## INSTALLATION CLEARANCES

Rear 25mm LH Side 25mm RH Side 25mm

## CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is required

## **MOFFAT**

Australia www.moffat.com.au New Zealand www.moffat.co.nz www.turbofanoven.com

### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +61 8-9413 2400 wasales@moffat.com.au

## New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management SGS Standard

Designed and manufactured by





## ISO9001


All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection. ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd AN.TFN.S.1901









an Ali Group Company

