

Technical data sheet for

## P85M8 PROVER/HOLDING CABINET

Full Size 8 Tray Electric / Manual Prover/Holding Cabinet



### P85M8

Unit shall be a Moffat electrically heated Turbofan Prover and Holding Cabinet. The prover and holding cabinet shall have double skin construction with stainless steel interior and exterior sides, front and top. Door shall be side hinged and field reversible. Unit shall have capacity for 8 18" x 30" trays, or 8 16" x 29" trays with optional 16" rack set. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinet shall be controlled by a mechanical thermostat and humidity via a control of the water tank. A thermometer shall indicate the cabinet temperature. Prover and holding cabinet shall be mounted on castors, with two rigid castors at rear and two swivel castors dual swivel and wheel lock and front. Prover and Holding cabinet shall operate independently or in combination with Moffat Turbofan model E35D or E35T Convection Ovens. Prover and Holding Cabinets shall be fitted with 13A cordsets. Unit shall be supplied in 100% recyclable shipping packaging.

### STANDARD FEATURES

- Dual function Prover and Holding Cabinet
- Designed for individual use or system installed with Turbofan E35D and E35T Convection Ovens
- 8 457mm x 762mm / 18" x 30" tray capacity
- 76mm tray spacing
- 910mm width
- 13A cordset fitted
- Full double skin construction
- Auto water fill system with optional integrated water filter kit
- Continuous door seal
- Side hinged door (standard LH hinge). Optional RH hinge (field convertible)
- Off / Proof / Hold mode selection
- Low velocity circulation fan system
- Mechanical thermostat
- Humidity level control
- Dual halogen cabinet interior lamps
- Cabinet temperature display thermometer
- 4 dia. 76mm castors with 2 front castors dual wheel and swivel lock, 2 rigid rear castors
- 100% recyclable packaging

### OPTIONS

- 406mm x 736mm / 16" x 29" tray rack set for prover

### ACCESSORIES

- Optional M236060 Core Temperature Probe Kit
- Optional 3M Cuno water filter kit complete with cartridge and connection fittings (Installs in pre-fitted rear housing of cabinet for flush rear installation)

### P85M8 Full Size Manual / Electric Prover/Holding Cabinet

#### CONSTRUCTION

304 stainless steel interior cabinet  
 Stainless steel front, sides and top exterior  
 Stainless steel interior side racks  
 Stainless steel frame side hinged door  
 5mm thick door glass  
 Stainless steel control panel  
 Aluminised coated steel base and rear panels

#### CONTROLS

Off / Proof / Holding mode selector switch.  
 Mechanical thermostat 20-85°C  
 Air heating ON control panel indicator  
 Humidity level control  
 Humidity tank ON control panel indicator  
 Cabinet temperature thermometer  
 Auto-fill water system standard

#### CLEANING

Stainless steel top and side exterior panels  
 Stainless steel interior chamber  
 Easy access to all interior surfaces  
 Fully removable stainless steel rack support  
 Removable humidity water tank (no tools)

#### SPECIFICATIONS

##### Electrical Requirements

230-240V, 50Hz, 1 phase, 1.5kW, 6.2A  
 13A cordset fitted

##### Water Requirements (optional)

Cold water connection 3/4" BSP male  
 80psi maximum inlet pressure / 20psi minimum inlet pressure

##### External Dimensions

Width 910mm  
 Height 914mm including dia. 76mm castors  
 Depth 880mm

##### Prover Internal Dimensions

Width 465mm  
 Height 730mm  
 Depth 795mm  
 Volume 0.27m<sup>3</sup>

##### Nett Weight (P85M8)

93kg

##### Packing Data (P85M8)

133kg  
 1.05m<sup>3</sup>  
 Width 950mm  
 Height 1070mm  
 Depth 1020mm

##### INSTALLATION CLEARANCES

Rear 25mm  
 LH Side 25mm  
 RH Side 25mm

##### CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is required



blue-seal.co.uk  
 turbofanoven.com

#### United Kingdom Blue Seal Limited

Unit 67  
 Gravelly Business Park  
 Gravelly  
 Birmingham B24 8TQ  
 England  
 Telephone 0121-327 5575  
 Facsimile 0121-327 9711  
 sales@blue-seal.co.uk  
 www.blue-seal.co.uk


#### Australia Moffat Pty Limited

740 Springvale Road  
 Mulgrave, Victoria 3170  
 Australia  
 Telephone 03-9518 3888  
 Facsimile 03-9518 3833  
 vsales@moffat.com.au  
 www.moffat.com.au

#### New Zealand Moffat Limited

Christchurch  
 45 Illinois Drive  
 Izone Business Hub  
 Rolleston 7675  
 Telephone +64 3-983 6600  
 Facsimile +64 3-983 6660  
 sales@moffat.co.nz  
 www.moffat.co.nz

Manufactured by:  
 Moffat Limited  
 45 Illinois Drive, Izone Business Hub  
 Rolleston 7675, New Zealand



Designed and manufactured by  
**MOFFAT**

#### ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.



© Copyright Moffat Ltd  
 UK.TFN.S.1601