



Classe 5 USB Tall - RC1G C5EVO BLK

RANCILIO CLASSE 5 USB TALL 1 GROUP



STANDARD FEATURES

- Tall deck accommodates tall cups up to 145mm in height includes step for espresso cups
- Single hot water tap with manual operation for full control
- Ergonomic portafilter holder up to 21g capacity, comfortable for allday operation
- C-Lever quarter turn steam tap features two positions: purge (down) or fully open (up)
- Hydro hub integrated manifold for precise water delivery and distribution
- · Multifunction onboard computer and USB port for simple programming and data transfer
- Water pump pressure control gauge that keeps you in control
- Built-in volumetric rotary vane water pump for simple and safe installation
- · Steam boiler pressure control with mechanical pressure stat
- · Automated cleaning programme simplifies your daily clean

OVERALL CONSTRUCTION

- · Hand rolled copper steam boiler 4 litre capacity
- Brushed stainless steel front and rear panels
- · Anthracite black ABS nylon side panels
- · Adjustable feet with optional extensions
- · Backflow valve on the boiler and steam tap

CONTROLS

- Soft-touch keypads with 4 programmable drink dosing pre-sets for easy espresso preparation
- White LED backlights easy to read keypad buttons
- · One manual steam wand for frothing and steaming milk

CLEANING AND MAINTENANCE

- Stainless steel drip tray dishwasher safe
- Easy Clean manages the cleaning process of group heads to perform automatically
- Genuine cleaning products sold separately

INCLUDES

- 1x Single group handle
- 1 x Single filter basket 16g
- 1x Double group handle
- 1 x Double filter basket 21a
- 1x Rubber blind filter disc
- 1x Group head cleaning brush
- User manual / Warranty card

MATCHING PRODUCTS



















Classe 5 USB Tall - RC1G C5EVO BLK

RANCILIO CLASSE 5 USB TALL 1 GROUP

TECHNICAL INFORMATION

Dimensions

Width: 410mm
Depth: 539mm
Height: 519mm
Nett weight: 37kg
Boiler Capacity: 4 litres

ELECTRICAL

Power requirements: 240V, 1P+N+E, 50/60Hz, 10A cordset fitted Boiler Power: 2.05kW



WATER CONNECTIONS AND DRAINS

- 40mm PVC drain and waste trap 300mm upstand
- Fixed water supply connection
- Mains cold water 3/8" BSP male thread connection
- Flow pressure: 200kPa -500kPa, min 4L/min

MOFFAT®

Australia www.moffat.com.au New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales

Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia

Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland

Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz









In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd AN.RAN.2301

RANCILIO WATER SPECIFICATION

Optimum Parameter	Measurement Range
TDS <135	Never more than 50 PPM more than to Total Hardness
Carbonate Hardness 50 ppm	40-90 ppm
Total Hardness 85 ppm	50-100 ppm
pH (ideal) 7	6.5 – 8.5
Chlorides CI -	< 30 ppm

INSTALLATION CLEARANCE

- Allow 152.4mm / 6" clearance on all sides of the machine.
- Allow 609mm x 127mm / 24" x 5" for in-line filter. Filter can be mounted behind the machine or under the counter.
- Allow a minimum of 3" (762 mm) clear space under filter to facilitate filter change.
- All services to be within 1m of machine placement
- Always refer to installation manual









