Waldorf Bold

Gas Cooktops 900mm

RNLB8600G-B, RNLB8600G-CD, RNLB8600G-LS, RNLB8600G-RB, RNLB8603G-B, RNLB8603G-CD, RNLB8603G-LS, RNLB8603G-RB, RNLB8606G-B, RNLB8606G-CD, RNLB8606G-LS, RNLB8606G-RB, RNLB8609G-B, RNLB8609G-CD, RNLB8609G-LS, RNLB8609G-RB, RNLB8609G-B, RNLB8609G-RB, RNLB8609G-RB,



RNLB8600G-CD

- Heavy-duty construction
- 28MJ/hr open burners
- Flame failure standard
- Pilot burners optional
- 300mm, 600mm, and 900mm griddle plate options
- Optional simmer plates
- 3 models of base unit
- 1 model of refrigerated base with two GN 1/1 drawers
- Stainless steel exterior
- Black vitreous enamel finish to front panels
- Easy clean
- Easy service
- Fully modular

Series Options

RNLB - Low back models RNB - 215mm splashback option

OVERALL CONSTRUCTION

- COOKTOP
- Welded hob with 1.5mm 304 stainless steel bull nose
- Splashback and side panels 1.2mm 304 stainless steel
 Front panels 0.9mm 304 stainless steel
- Front panels 0.9mm 304 stamless steel
 Cast iron 28MJ/hr open burners with forged brass cap
- Vitreous enamelled cast iron potstands
- Stainless steel open burner spill covers
- Cast iron simmer plates (optional extra)
- 12mm thick mild steel griddle plate
- 2.5mm 304 stainless steel griddle splash guards
- Stainless steel spill trays
- Griddle sections are standard on RH side. Available on LH side to order or by conversion.

BENCH MOUNT (SUPPLIED AS -B MODEL)

- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet.
- Adjustable height 80mm 105mm
- CABINET BASE (SUPPLIED AS -CD MODEL)
- Fully modular for match suite finish
- Double skin 0.9mm 304 stainless steel interior and exterior
- Optional GN 1/1 4 position racking kit (1 or 2 cabinet bays)
- Up to eight 65mm GN 1/1 capacity
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjust. feet
- LEG STAND (SUPPLIED AS -LS MODEL)
- Fully modular for matched suite finish
 Framed top for connection to Consistent
- Framed top for connection to Cooktop
 63mm dia, heavy-duty 1,2mm 304 staipless s
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjust. feet
 Fully modular framed stand shelf with 0.9mm 304 stainless steel finish
- Shelf to top stainless steel backstop panel for convenience and rigidity
- Suitable for rear or through shelf gas connection to Cooktop
- · Quick assembly design (no tools required)

REFRIGERATED BASE (SUPPLIED AS -RB MODEL)

- · Self contained suite matched modular base
- Ventilated system with R134a refrigerant
- -2° to + 8°C temperature (Tropical Climate rated)
- Two GN 1/1 drawers
- 100mm deep pan drawer capacity
- Heavy-duty European telescopic drawer guides
- Magnetic drawer gaskets (replaceable without tools)
- 50mm fully foamed CFC free insulation
- 304 stainless steel exterior and interior
- Anti-corrosion treated evaporator
- No condensate drain required
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjust. feet Condensing unit removable through front of unit for service
- Easy clean interior
- Refrigerated bases in stainless steel finish only

CONTROLS

COOKTOP

- Variable high to low controls to open burners
- Open burners flame failure standard with pilot burners optional
- Variable high to low controls to griddles
- · Griddles standard with pilot, flame failure and piezo ignition
- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

REFRIGERATED BASE


- Digital control electronic thermostat
- Automatic defrost
- Automatic evaporation of defrost water
 -2° to +8°C temperature range

- CLEANING AND SERVICING
- All models with easy clean stainless steel external finish
- Lift off burner heads
- Stainless steel spill trays under open burner and griddle sections
 Access to all parts from front of unit
- Refrigerated Base condenser removable through front of unit




Gas Cooktops 900mm

RNLB8600G-B



RNLB8600G-LS





RNLB8600G

SPECIFICATIONS

Open Burners 28MJ/hr dual flame ring with

Griddle Burners 20MJ/hr per 300mm section

Gas power (gross) RNLB8600G 168MJ/hr, 46.6kW RNLB8603G 132MJ/hr, 36.6kW

RNLB8606G 96MJ/hr, 26.6kW

RNLB8609G 60MJ/hr, 16.6kW

300mm Griddle cooking surface

600mm Griddle cooking surface 592mm x 475mm, 2812cm2

900mm Griddle cooking surface

130mm from RH side, 32mm from rear,

All units supplied with Natural and LP gas

292mm x 475mm, 1387cm2

892mm x 475mm, 4237cm2



Burners

simmer rate

Griddle Plate

Gas connection

R ¾ (BSP) male

regulator

and 655mm from floor

Type Ventilated system

Electrical connection

Refrigerated base





RNLB8600G-CD

RNLB8600G-RB

900

00 00 00

130

00

T 130

00 00

70

GAS ENTBY

33

32

ELECTRICAL ENTRY

100

GAS ENTRY

322

402

136 490

70

20 15



All models (excluding Bench model) Cabinet Base and Refrigerated Base models 1.03m3, 245kg (180kg nett) Width 945mm Other gas types on request

OPTIONS AT EXTRA COST

Simmer plates (replaces Potstand) Ribbed griddle plates Joining caps Castors Plinth mounting

an Ali Group Company



moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone -613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





MOFFAT

ISO9001

All Waldorf Bold products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.WBD.S.01.2020



Width 900mm Depth 805mm Height 915mm Incl. low back 970mm Incl. splashback option 1130mm Packing data Bench and Leg Stand models 0.55m3, 174kg (129kg nett) Width 945mm Depth 870mm Height 665mm

Depth 870mm Height 1255mm Gas types Available in Natural gas and LP gas Please specify when ordering Units supplied complete with gas type conversion kits

3 pin 10A plug cordset fitted Dimensions Bench models Width 900mm Depth 805mm Height 315mm Incl. low back 370mm

Incl. splashback option 530mm

Refrigerant R134a (160grams) Climate classification T – tropical

220-240Vac, 50Hz, 1.8A, 1P+N+E