

SF180

8 4 U





GUIDES	WEIGHT	EFFECT	TARGET TEMPERATURE	S: -	F: 80°C
4+8 x GN 1/1 80mm spacing	62kg	Neutral + 230V/550W	TEMPERATURE RANGE:	S: -	F: 40 - 90°C
			EXTERIOR WALLS:	ABS plastic.	
OUTER	R INNER S INNER F		INNER CONTAINER:	Welded container in stainless steel.	
B: 525mm D: 770mm	B: 330mm D: 540mm	B: 330mm D: 540mm H: 670mm	GUIDES:	Stainless steel, pressed from the inner container.  Maximum load per pair of guides is 30 kg.	
H: 1445mm	H: 350mm		INSULATION:	Polyurethane.	
122111-ZSF SDX Thermobox SF180 (4+8 GN 1/1) One grip handle 122111-XSF SDX Thermobox SF180 (4+8 GN 1/1) Eccentric lock			DOOR:	Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.	
			WHEELS:	160 mm wheels, two brakeable and two fixed.	
			TOP FRAME:	A stable and protective frame with PVC corners.	
			TROLLEY FRAME:	Impact protection bumper of stainless steel coated with PVC.	
			S:	Neutral, insulation class IP55.	
			F:	Efficient convection heating system, with electronic temperature control. IP55 rated.	

TRANSPORTATION OF HOT AND COLD FOOD IN A HYGIENIC AND SUSTAINABLE WAY FOR BOTH HUMANS AND THE ENVIRONMENT