



DOX30, DOX30G

Water Meter

Product Features

- Control box in 4mm thick PVC and stainless steel
- · Microprocessor logic with permanent memory
- Keys up and down for setting the quantity
- START key for starting or resuming water delivery
- STOP/C key for manual stop or eventual clearing of memory
- Digital display for selected, yet to be delivered (during batching), or al ready discharged (after pressing STOP) water quantity
- Digital display of electronic internal thermometer, showing °C, or °F
- Series of function control lights
- Double stainless steel net filter for water impurities
- No-return valves
- Remote pump control (pre-assembled cable)
- 2.5 metre delivery hose with stainless steel terminals
- Internal fittings only of bronze, brass and stainless steel



Take better control of your mixing environment with our range of STM water dosing meters. Manufactured in Italy to exacting standards, STM water meters are designed to dose water accurately, consistently and reliably. With options available that include simple water dosing, water temperature blending and dosing, programmable water temperature blending and dosing the STM range of products will prove the best solution for your bakery.





DOX30, DOX30G

Water Meter

Model DOX30

Dimensions

Width 380mm
Depth 146mm
Height 396mm

Electrical Requirements
220-240V, 1P+N+E, 50Hz, 25W

Model DOX30G

Dimensions

Width 380mm
Depth 146mm
Height 396mm

Electrical Requirements
220-240V, 1P+N+E, 50Hz, 25W

It is a Water Doser-Mixer with microprocessor electronics, equipped with a keyboard with tactile sensation for setting the water quantity and with digital displays for the quantity and for the delivery temperature. Mixing is automatic thermostatic. It doses and mixes warm and pipe water; warm and refrigerated water; refrigerated and pipe water; warm, refrigerated and pipe water (according to the type of installation) to obtain the desired water quantity at the desired temperature.

- Digital display for selected, yet to be delivered (during batching), or already discharged (after pressing STOP) water quantity
- Digital display of electronic internal thermometer, showing °C or °F
- · Series of function control lights
- Remote pump control (pre-assembled cable)
- No-return valves
- 2.5m delivery hose (10), with stainless steel terminals
- Internal fittings only of bronze, brass and stainless steel
- Mixing is by automatic thermostatic valve, adjusted manually by the operator (DOX30G)

moffat.com.au moffat.co.nz

Australia

moffat.com.au Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales

Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia

Telephone +613-9518 3888 vsales@moffat.com.au

Queensland

Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

This specification sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

© Copyright Moffat Ltd AN.S.01.21

an Ali Group Company

