





## STANDARD FEATURES

1, 2 and 3 minute cycles

Compatible with 365mm to 500mm racks

Wash capacity of up to 1,080 plates per hour

Touchscreen controls providing advanced customisation

0.5HP soft start wash pump

Dual chemical pumps

Hands-free drainage system with sump and drain pump Heavy-duty stainless steel scrap tray and waste basket Customisable auto-drain and self-cleaning functionality

Adjustable tilting rack slide Independent wash and rinse arms

Heavy-duty stainless steel construction

1x 500mm dish rack (600 70028)

1x 500mm cup rack (600 70029)

1x cutlery container (C660503)

1x quick connection kit (all hoses and 1p/15A plugset)

## SPECIFICATIONS

_	-	_	_		-			-	_	-	
Δ	. –	ŀ	10	ot	١	Na	te	21	-		

Temperature	65°C

Connection 3/4" male, hose supplied

Pressure 200-500kPa Flow 20L per minute

Backflow prevention Atmospheric vacuum breaker

Consumption 2.2L per cycle\*


## D - Drainage


Drain pump flexi-hose 25mm


C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	3.37

Isolating switch must be within 1m of, and not directly behind, the machine Refer to operator manual for installation instructions

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.







Dimensions	Machine	Packed
Width (mm)	570	620
Depth (mm)	600	675
Height (mm)	840	940
Weight (kg)	75	78
Volume (m3)		0.39

Water Quality	Min	Max
рН	7	8
TDS	1	135
CI-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

<sup>\*</sup>Water consumption rates my vary based on site conditions









an Ali Group Company

