

# Craftsman

---

VF60

Vari Filler Depositor - Variable Speed

W 600mm x D 820mm x H 1200mm

## Product Features

- General purpose depositor
- Holding tank capacity of 60 litres
- Designed for hot fillings up to 100°C or ambient fillings
- Accuracy level of +2grams (Depending on product)
- Up to 80 deposits per minute
- There are many applications for this unique unit including: pies, sausage rolls, vegetable rolls and turnovers of all types






VF60

# Craftsman

---

## VF60 Vari Filler Depositor - Variable Speed



VF60 Speed Control, Handle & Spout

### Other product uses include:

- Juice
- Sauces
- Creamy syrups
- Whipped potato
- Fondants and other hot products
- Non aerated cake batters
- Icing
- Pasta fillings
- Cheese sauces
- Chunky meat and vegetable fillings  
(max 8mm hard & 12mm soft pieces)
- Diced fruit (max 10mm cubed)
- Shredded vegetables

NOTE: Not suitable for aerated products



Australia  
[www.moffat.com.au](http://www.moffat.com.au)  
New Zealand  
[www.moffat.co.nz](http://www.moffat.co.nz)

Australia  
Moffat Pty Limited

Victoria/Tasmania  
740 Springvale Road  
Mulgrave, Victoria 3170  
Telephone 03-9518 3888  
Facsimile 03-9518 3833  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)  
[www.moffat.com.au](http://www.moffat.com.au)

New South Wales  
Telephone 02-8833 4111  
[nswsales@moffat.com.au](mailto:nswsales@moffat.com.au)

South Australia  
Telephone 03-9518 3888  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

Queensland  
Telephone 07-3630 8600  
[qldsales@moffat.com.au](mailto:qldsales@moffat.com.au)

Western Australia  
Telephone 08-9202 6820  
[bgarcia@moffat.com.au](mailto:bgarcia@moffat.com.au)

New Zealand  
Moffat Limited

Christchurch  
16 Osborne Street  
Christchurch 8011  
Telephone 03-389 1007  
Facsimile 03-389 1276  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)

Auckland  
Telephone 09-574 3150  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)

### Dimensions

Width: 600mm  
Depth: 820mm  
Height: 1200mm

### Volume

60 litres

### Electrical Requirements

240V, 1P+N+E, 50Hz, 0.75kW

### Weight Range

20grams (minimum)

