



# WD-7CH ERGONOMIC PASSTHROUGH DISHWASHER WITH CONDENSING UNIT

### STANDARD FEATURES:

- Including condensing unit with heat recovery by exhaust steam
- Washes up to 50 baskets per hour
- 2.5 litres per cycle water consumption
- 50 litre wash tank volume
- Unique hood designed for steam to escape at the back of machine
- Simple program selection 3 levels of wash cycle for varying types of soiled products
- Auto Start function
- Electronic control panel with event log recording for diagnostics
  and trouble shooting
- Automatic cleaning program
- Self-draining wash arms for optimum wash results
- 1.1kW wash pump with 9kW booster heater
- Fixed basket conveyor designed for improved washing results
  and cleaning
- Smooth internal surfaces for easy cleaning
- Stainless steel construction
- Corner or in-line installation
- Automatic hood lift
- Drain pump
- Detergent and rinse aid pumps for liquid detergent
- Supplied with 3 high quality dish racks

Upgrades and options are available, please contact Moffat for more details

## TECHNICAL INFORMATION:

Dimensions Width: 600mm Depth: 739mm Height: 2247mm Water COLD WATER ONLY Connection: R ½" Direct Pressure: 180kPa Flow: 10 litres per min Water quality (Hardness): 2-7odH

#### Waste

Drain hose connection point Drain Flow: 3 litres per second

#### Electrical

3P+N+E 400-415V 50/60Hz 10.1kW 16A Cordset supplied Refer operator manual for complete installation instructions



#### Australia


moffat.com.au Moffat Pty Limited 740 Springvale Road Mulgrave Victoria 3170 Australia Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

# New Zealand

moffat.co.nz Moffat Limited 45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand Telephone +64 3-983 6600 Saclsmile +64 3-983 6660 sales@moffat.co.nz


In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.





660

Top view:



. Electrical connection, external thread R1/2" 3-5 Bar 3. Drain 950 31/sec 4. Plugged hole for detergent connection 5. Air bleeding screw lift cylinder 6. Water output detergent dosing

#### © Copyright Moffat Ltd AN.WDK.SS.1701

an Ali Group Company

G R O U P The Spirit of Excellence