

## WD-B700S FLIGHT TYPE DISHWASHER

### STANDARD FEATURES:

- 4105 plates per hour standard up to 5696 plates per hour depending on configuration according to DIN10510
- 190 litres per hour cold water consumption for normal final rinse
- Loading zone - 1125mm
- Pre-wash zone - 1000mm
- Chemical wash zone – 2000mm
- Double final rinse zone – 1125mm
- Drying zone – 875mm
- Unloading zone – 1500mm
- Total length 7625 mm
- Multiple size options for Loading / Unloading zones
- Condensate coil and heat exchanger to simultaneously reduce heat emissions and heat incoming cold water
- Water automatically turns off in each zone when there is no dishes
- Touchscreen controls with 6 speeds/wash times
- Double heat recovery
- Fully insulated doors and panels
- Ergonomically designed, for ease of use and cleaning

Upgrades and options are available, please contact Moffat for more details

### TECHNICAL INFORMATION:

#### Dimensions

Width: 7625mm  
Depth: 1013mm  
Height: 1920mm

#### Water

Hot water temperature: 50-70°C  
Hot water connection: R¾"  
Cold water temperature: 5-12°C  
Cold water connection: R¾"  
Pressure: 300-600kPa  
Flow: 18 litres per min  
Water quality (Hardness): 2-7odH

#### Waste

Connection: 50mm dia


#### Electrical

3P+N+E 400-415V 50/60Hz  
39.3kW 80A

**Steam Heated** 50-140 kpa  
3P+N+E 400-415V 50/60Hz  
13kW 35A

**Steam Heated** 150-250 kpa  
3P+N+E 400-415V 50/60Hz  
13kW35A

Refer operator manual for complete installation instructions



Size	Type	WD-B700S
A	(length)	7625
B		2300
C		1625
D		4190
E		1810
F		2825
G		2895
H		2980
I		2375

1. Extractor 600x70 mm without damper. Air quantity, see technical specs
2. Extractor 400x50 mm without damper. Air quantity, see technical specs
3. Electrical connection from ceiling, alternative electrical connection from floor, see point 9
4. Hot water connection \*
5. Cold water connection \*

6. Steam connection \* (steam-heated machine)  
Steam pressure 150-250 kPa (Electrically heated drying zone)  
Steam pressure 50-140 kPa (Electrically heated drying zone)
7. Condensation water connection (steam-heated machine)
8. Floor drain 400x600 mm
9. Through channel for alternative electrical connection from floor and / or water connection from above

\* Connection from floor or ceiling

### Australia

[moffat.com.au](http://moffat.com.au)

Moffat Pty Limited  
740 Springvale Road  
Mulgrave  
Victoria 3170  
Australia  
Telephone +613-9518 3888  
Facsimile +613-9518 3833  
vsales@moffat.com.au

### New Zealand

[moffat.co.nz](http://moffat.co.nz)

Moffat Limited  
45 Illinois Drive  
Izone Business Hub  
Rollestone 7675  
New Zealand  
Telephone +64 3-983 6600  
Facsimile +64 3-983 6660  
sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.