

WD-B900S FLIGHT TYPE DISHWASHER

STANDARD FEATURES:

- 5430 plates per hour standard up to 7535 plates per hour depending on configuration according to DIN10510
- 210 litres per hour cold water consumption for normal final rinse
- Loading zone - 1125mm
- Pre-wash zone - 1000mm
- Chemical wash zone - 3000mm
- Double final rinse zone - 1125mm
- Drying zone - 1500mm
- Unloading zone - 1500mm
- Total length 9250 mm
- Multiple size options for Loading / Unloading zones
- Condensate coil and heat exchanger to simultaneously reduce heat emissions and heat incoming cold water
- Water automatically turns off in each zone when there is no dishes
- Touchscreen controls with 6 speeds/wash times
- Double heat recovery
- Fully insulated doors and panels
- Ergonomically designed, for ease of use and cleaning

Upgrades and options are available, please contact Moffat for more details

TECHNICAL INFORMATION:

Dimensions

Width: 9250mm
Depth: 1013mm
Height: 1920mm

Water

Hot water temperature: 50-70°C
Hot water connection: R¾"
Cold water temperature: 5-12°C
Cold water connection: R¾"
Pressure: 300-600kPa
Flow: 18 litres per min
Water quality (Hardness): 2-7odH

Waste

Connection: 50mm dia


Electrical

3P+N+E 400-415V 50/60Hz
54.9kW 100A

Steam Heated 50-140 kpa
3P+N+E 400-415V 50/60Hz
18kW 50A

Steam Heated 150-250 kpa
3P+N+E 400-415V 50/60Hz
18kW 50A

Refer operator manual for complete installation instructions



Size	Type	WD-B900S
A	(length)	9250
B		2925
C		1625
D		5815
E		1810
F		3450
G		3520
H		3605
I		3000

1. Extractor 600x70 mm without damper. Air quantity, see technical specs
2. Extractor 400x50 mm without damper. Air quantity, see technical specs
3. Electrical connection from ceiling, alternative electrical connection from floor, see point 9
4. Hot water connection *
5. Cold water connection *

6. Steam connection * (steam-heated machine)
Steam pressure 150-250 kPa (Electrically heated drying zone)
Steam pressure 50-140 kPa (Electrically heated drying zone)
7. Condensation water connection (steam-heated machine)
8. Floor drain 400x600 mm
9. Through channel for alternative electrical connection from floor and / or water connection from above

* Connection from floor or ceiling

Australia

moffat.com.au

Moffat Pty Limited
740 Springvale Road
Mulgrave
Victoria 3170
Australia
Telephone +613-9518 3888
Facsimile +613-9518 3833
vsales@moffat.com.au

New Zealand

moffat.co.nz

Moffat Limited
45 Illinois Drive
Izone Business Hub
Rollestone 7675
New Zealand
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.