





STANDARD FEATURES

1, 2 and 3 minute dishwashing cycles
2.2L per cycle water consumption
Compatible with 500mm racks
Washes up to 1,080 dishes per hour
Adjustable benchgap of 595mm to 640mm
Washtech hybrid controls
Easy change to higher power / rapid rinse recovery mode
Hands-free auto-drain with drain pump

1.0HP wash pump and dual chemical pumps Heavy duty stainless steel wash manifold and scrap trays

Includes

1x 500mm dish rack (600 70028) 1x 500mm cup rack (600 70029) 1x cutlery container (C660503) Quick connection kit (all hoses and 15A plugset)

Stainless steel wash and drain filter

SPECIFICATIONS

A - Hot Water	
Temperature	65°C
Connection	3/4" male, hose supplied
Pressure	200-350kPa
Flow	20L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.2L per cycle*
•	


D - Drainage


mm

C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	3.25
Single phase	230-240	50	25	5.75
Three phase	400-415	50	15	7.50

*Water consumption rates my vary based on site conditions Isolating switch must be within 1m of, and not directly behind, the machine Refer to operator manual for installation instructions


In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.











Machine	Packed
730	760
710	820
1530	1460
94	125
	0.91
	730 710 1530

Water Quality	Min	Max
рН	7	8
Hardness	20	100
CI-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

Corner installation: machine must face left for access to controls; allow 300mm front clearance for service access; and splashback return <150mm.

Inline installation: front panels can be adjusted to 605mm leaving upper 80mm sill only at 650m; for sites requiring full cabinet <650mm, order WXP0031.









an Ali Group Company

