



Merrychef Rapid High Speed Cook Oven

e1s



Standard Features


- Compact 407mm wide footprint fits on a 500mm bench depth
- Plug & Play single 15A power supply
- Oven cavity to suit up to 306mm x 308mm / 12" plate size
- Best in class energy efficiency less than 0.7kWh in standby mode
- Rapid cooking up to 10-12 times faster than a conventional oven
- Rapid cooking technology combines three heat technologies: tuned impingement, microwave and convection heat
- · Ventless cooking capabilities through built in catalytic converter
- Fast heat up and cool down
- Colour easyTouch® icon driven touch screen control panel with the capability of storing up to 1024 multi-stage recipe programs
- Each program offers up to six (6) stage with programmable cooking times, microwave power setting and user instructions for each stage
- Easy menu updates or data transfer via USB
- Built in diagnostic testing
- Optimum time management with automatic On & Off timers
- Precise temperature setting range from 100°C 260°C
- Quiet operation 52dbA in standby mode
- Black exterior on stainless steel
- Cool to touch exterior allows for zero space at the sides and back
- Easy access to front mounted air filter
- Easy to clean cavity with large rounded edges

Includes

- Solid cook plate
- · Guarded paddle with sides
- Cook plate liner
- · Solid base basket
- · Cleaning care package, consisting of:
 - 1x oven cleaner (bottle)
 - 1x oven protector (bottle)

Accessories

- Baskets
- Cook plates
- · Cook plate liners
- Paddles
- Racks




How it works

The convection fan pulls air in through the back of the cavity (1). This is then heated and returned to the cavity through the catalytic converters (2) and impinger plate (3) to produce an even heat pattern in the oven. This heat pattern allows food to cook evenly and produces a crisp golden finish every time.




Merrychef Rapid High Speed Cook Oven

elkon° e1s







MOFERT

Australia moffat.com.au

New Zealand moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Ph 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales Ph 02-8833 4111 nswsales@moffat.com.au

South Australia Ph 03-9518 3888 vsales@moffat.com.au

Queensland Ph 07-3630 8600 qldsales@moffat.com.au

Western Australia Ph 08-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

2.99 kW

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Ph +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.MC.1810



MICROWAVE POWER

Microwave settings, off or 5-100% in 1% increments Distribution system, rotating active antennae

CONVECTED HEAT

Temperature settings OFF and from 100° to 260°C in 1°C steps

Distribution system, Tuned Impingement

DIMENSIONS

Width 407mm
Depth 538mm
Height 588mm
Weight 46kg

PACKED DIMENSIONS

 Width
 774mm

 Depth
 604mm

 Height
 719mm

 Weight
 61kg

INSTALLATION REQUIREMENTS

 Rear
 0 mm

 Right
 0 mm

 Left
 0 mm

 Top
 50 mm

INSTALLATION REQUIREMENTS

For precise installation instructions please refer to the units installation manual

ELECTRICAL SUPPLY

Single phase model 230-240V, 50Hz (1P + N + E) Rated power consumption Rated current

Rated current 15A All Merrychef ovens require installing a type D circuit breaker for all installations.

POWER OUTPUT (APPROX.)

Microwave 0.8kW
Convected heat 2.2kW
Combination mode 0.8** + 0.9kW

** This is approximate microwave power output.

